



## Description

### GigE Vision camera, 2 Megapixels and 30 fps, Sony ICX274, PoE option


The Manta G-201B/C-30fps is a fast GigE Vision camera with a Sony ICX274 sensor. It runs at 30 fps (full resolution). With a smaller ROI, higher frame rates are possible. It incorporates three LUTs, sophisticated color correction algorithms, a robust metal housing, and many modular options like angled heads or board level versions. Manta cameras cover a wide range of imaging applications. The Manta is **now optionally available with PoE (Power over Ethernet).**

- Sony ICX274 (type 1/1.8), 2 Megapixels
- Sync modes
  - Trigger ready, trigger input, exposing, readout, imaging, strobe, GPO
- Trigger
  - External trigger event: rising/falling/any edge, level high/low
  - External trigger delay: 0 to 60 seconds in 1  $\mu$ s increments
- Modular options
  - Various IR cut/pass filters
  - CS-Mount
  - Board level version
  - Angled head
  - White medical housing
  - **NEW: PoE (Power over Ethernet)**

## Specifications

<b>Manta</b>		<b>G-201-30fps</b>	
<b>Interface</b>	IEEE 802.3 1000baseT		
<b>Resolution</b>	1624 x 1234		
<b>Sensor</b>	Sony ICX274		
<b>Sensor type</b>	CCD Progressive		
<b>Sensor size</b>	Type 1/1.8		
<b>Cell size</b>	4.4 µm		
<b>Lens mount</b>	C/CS		
<b>Max frame rate at full resolution</b>	30 fps		
<b>A/D</b>	14 bit		
<b>On-board FIFO</b>	32 MB		
<b>Output</b>			
<b>Bit depth</b>	8-12 bit		
<b>Mono modes</b>	Mono8, Mono16, Mono12 packed		
<b>Color modes YUV</b>	YUV411, YUV422, YUV444		
<b>Color modes RGB</b>	RGB24, BGR24		
<b>Raw modes</b>	Bayer8, Bayer16, Bayer12 packed		
<b>General purpose inputs/outputs (GPIOs)</b>			
<b>Opto-coupled I/Os</b>	2 inputs, 2 outputs		
<b>RS-232</b>	1		
<b>Operating conditions/Dimensions</b>			
<b>Power requirements (DC)</b>	8 V - 30 V		
<b>Power consumption (12 V)</b>	4.6 W		
<b>Mass</b>	<200 g		
<b>Body Dimensions (L x W x H in mm)</b>	86.4 x 44 x 29 mm incl. connectors		
<b>Regulations</b>	CE, FCC Class B, RoHS		

[Download Manta technical drawing \(click here\)](#)



## Smart features

- ROI (Region of Interest Readout)
- Exposure
  - Auto/one push/programmable
  - Exposure time 10  $\mu$ s to 60 s
- White balance
  - Auto/one push/programmable
- On-board debayering
- Hue, saturation, sharpness (color versions)
- Gain
  - Auto/one push/programmable
  - Manual gain control: 0 to 31 dB (1 dB/step)
- Three look-up tables (LUTs), gamma correction
- DSP subregion (selectable ROI for auto features)
- Binning (up to 8 x 14, independent x and y binning)
- Sub-sampling (decimation)
- Stream hold
- StreamBytesPerSecond (easy bandwidth control)
- Event channel
- Chunk data
- 5 storable user sets

## Applications

The Manta G-201B/C-30fps is a fast GigE Vision camera with PoE option. Thanks to its flexibility (angled head, board level version with separate sensor head), it can be used for a variety of applications. The Manta incorporates three LUTs (separate R, G, and B control), color correction, and many more features.

Typical applications:

- Machine vision
- ITS (Intelligent Traffic Solutions)
- Entertainment and multimedia applications
- 3D applications
- ITS (Intelligent traffic solutions)
- ... and many more