

Dual VGA Splitter

Ref. DVS

PC Distribution Amplifier



DVS at a glance

- > Displays Computer and Video Signals on up to 2 monitors
- > The same image can be displayed on 2 screens (Same type)
- > Fast and Flexible solution for presentations
- > Low Cost
- > Ultra-Compact

Features

- 200 MHz bandwidth
- Metal enclosure
- Ultra-Compact
- External power supply

Reference

- > [DVS](#): Dual VGA Splitter

Technical Specifications

Input

- Signals from any PC (VGA to UXGA)
- RGB S, RGBHV, (RGB 0.7V Analog - 75 Ohms)
- Sync : Composite, 5V TTL - H & V separated, 5VTTL / Hi. Z
- Line frequency from 15 kHz to 95 kHz
- Frame frequency from 40 Hz to 120 Hz
- Video bandwidth: 200MHz
- Connector: 15 Pin HD male

Outputs

- 2 separate and buffered outputs: RGBS, RGBHV
- RGB: 0.7V p/p: Composite and H & V Sync: 5V TTL
- Impedance: RGB = 75 Ohms
- Connectors: 15 pin HD female

Power Supply

External Power Universal Supply, 100-250 VAC, 50/60Hz, 5W

Supplied with

- 1 x AC power supply
- 1 x User manual*

Dimensions

- D 2.87" x W 4.76" x H 1.7"
- D 73 mm x W 121 mm x H 43 mm

Weight

- 0.7 kg / 1.54 lbs

Warranty

3 year warranty on parts and labor, back to factory

[Specifications subject to change without prior notice](#)

* Download on our website: www.analogway.com/technical-support/



ANALOG WAY®

Europe, Middle East and Africa
ANALOG WAY SAS
Tel. 331 64 47 16 03
Fax. 331 64 47 14 73
Email: saleseuro@analogway.com

USA, Canada, South America and The Carribeans
ANALOG WAY Inc.
Tel. 212 269 1902
Fax. 212 269 1943
Email: salesusa@analogway.com

DVS-122310-V2

Asia Pacific
ANALOG WAY Pte Ltd
Tel.: 65 62 92 58 00
Fax.: 65 62 92 52 05
Email: sales@analogwayasia.com