

T8125 AC 24V MIDSPAN 60W



Main Features

- Input Voltage: 24 V AC
- Maximum Output Voltage: 55 V DC
- Maximum Output Power: 60 W
- Input Ports: 1 10/100/1000Base-T
- Output Ports: 1 10/100/1000Base-T
- Height: 1.7"
- Width: 3.3"
- Depth: 6.5"
- Weight (Approximate): 1 lb
- Compatibility: Axis Q6035-E PTZ Dome Network Camera
- Certifications & Standards:
 - IEEE 802.3at, IEEE 802.3af, CE, FCC Part 15, Class B, EN 55022 Class B, EN 55024, VCCI, KCC, C-tick, CB, UL/cUL per EN 60950-1, GS Mark per EN 60950-1
- Green Compliant: Yes
- Green Compliance Certificate/Authority: RoHS, WEEE
- Limited Warranty: 3 Year

Marketing Information

Easier and faster installations Axis High Power over Ethernet midspans and splitters offer an easy, fast and cost-effective solution for powering network video products - specifically PTZ (pan/ tilt/ zoom) and PTZ dome network cameras - without the need to install power outlets and electrical cabling. Axis High Power over Ethernet (High PoE) midspans and splitters enable Axis network video products to receive data and power over the same Ethernet cable. The High PoE products make it easier to install network video products in areas where power cabling and outlets are unavailable. Installation costs are thus reduced.

Package Contents

- T8125 AC 24 V Midspan 60 W
- 2-pin AC Terminal Connector

Information

- Name:T8125 AC 24V MIDSPAN 60W
- Category:POE Midspans/Injectors/Repeaters
Networking
- UPC Code:7331021004665