

SONOFIL/OFC-Y 2x2.50 P
Code - 10002



Description

Oxygen free copper conductor. PVC outer sheath.

PHYSICAL CHARACTERISTICS

Conductor

Material	Oxygen free copper
Section (mm ²)	2,50
AWG	26
Composition	301 x 0,1

Outer shield

Material	PVC
Diameter (mm)	3,8 x 7,2
Colour	Transparent

Printing

Inscription	Conducfil
-------------	-----------

Supply

Packing	To be defined
---------	---------------



SONOFIL/OFC-Y 2x2.50 P
Código - 10002

MECHANICAL CHARACTERISTICS

Appox. Weight	67,4 Kg/km
Operating temperature range	-20 / +80
Minimum bending radius	38

ELECTRICAL CHARACTERISTICS

Conductor DC resistance at 20° C	7,3 Ohms/km
Nominal capacitance	216 pF/m
Insulation resistance	
Voltage test	1500 v

SAFETY

FLAME TEST

		Compliance
Test for vertical flame spread	IEC-60332-1	<input type="checkbox"/>
Test for vertical flame spread	IEC-60332-2	<input type="checkbox"/>
Test for vertical flame spread	IEC-60332-3	<input type="checkbox"/>
It does not emite toxic fumes or halogens	IEC-754-1	<input type="checkbox"/>
It does not emite corrosive fumes or halogens	IEC-754-2	<input type="checkbox"/>
Low emision of dense fumes	IEC-1034-1	<input type="checkbox"/>

ENVIRONMENT

		Compliance
Content of hazardous sustances	Directive 2002/95/CE	<input checked="" type="checkbox"/>

APPLICABLE SPECIFICATIONS

		Compliance
Conductor material	UNE-EN 60228	<input checked="" type="checkbox"/>
Insulation material	UNE-EN 50290	<input checked="" type="checkbox"/>