

TRIAX/SF-11 1x1.16 G
Code - 10389



Description

Silvered copper conductor. Physical foam polyethylene insulation. Silvered copper braid shield. TPE inner sheath. Bare copper braid shield. PVC-NBR outer sheath.

PHYSICAL CHARACTERISTICS

Conductor

Material	Silvered copper
Section (mm ²)	1,16
AWG	
Composition	19 x 0,28

Insulation

Material	Physical foam polyethylene
Diameter (mm)	6,50
Colour	natural

Inner shield

1st Shield	
Material	Silvered copper braid
Coverage	90 %

Inner sheath

Material	TPE
Diameter (mm)	8,5
Colour	Natural

Outer shield

1st Shield	
Material	Bare copper braid
Coverage	80 %



TRIAX/SF-11 1x1.16 G
Code - 10389

Outer sheath

Material	PVC-NBR
Diameter (mm)	11
Colour	Red

Printing

Inscription	Conducfil
-------------	-----------

Supply

Packing	To be defined
---------	---------------

MECHANICAL CHARACTERISTICS

Appox. Weight	130,5 Kg/km
Operating temperature range	-20 / +80
Minimum bending radius	220 mm

ELECTRICAL CHARACTERISTICS

Conductor DC resistance at 20° C	15 Ohms/km
Shield DC resistance at 20° C	6,3 / 5,0 Ohms/Km
Nominal capacitance	54 pF/m
Nominal impedance	75 ohms
Velocity of propagation	82 %

Attenuation	Frequency (MHz)	dB/100 m
	1	0,5
	10	1,9
	20	2,7
	100	4,6



TRIAX/SF-11 1x1.16 G
Code - 10389

Return loss	Frequency (MHz)	dB
	0-800	20
	800-1000	23
Insulation resistance	>5000 Mohms * Km	
Voltage test	1500 v	

SAFETY

FLAME TEST

		Compliance
Test for vertical flame spread	IEC-60332-1	<input type="checkbox"/>
Test for vertical flame spread	IEC-60332-2	<input type="checkbox"/>
Test for vertical flame spread	IEC-60332-3	<input type="checkbox"/>
It does not emite toxic fumes or halogens	IEC-754-1	<input type="checkbox"/>
It does not emite corrosive fumes or halogens	IEC-754-2	<input type="checkbox"/>
Low emision of dense fumes	IEC-1034-1	<input type="checkbox"/>

ENVIRONMENT

		Compliance
Content of hazardous sustances	Directive 2002/95/CE	<input checked="" type="checkbox"/>

APPLICABLE SPECIFICATIONS

		Compliance
Conductor material	UNE-EN 60228	<input checked="" type="checkbox"/>
Insulation material	UNE-EN 50290	<input checked="" type="checkbox"/>