

**COAXIAL/R-02YCY 1x0.35 S**  
**Code - 1948**



**Description**

Tinned copper conductor. Foam polyethylene insulation. Tinned copper braid shield. PVC outer sheath.

**PHYSICAL CHARACTERISTICS**

**Conductor**

Material	Tinned copper
Section (mm <sup>2</sup> )	0,10
AWG	27
Composition	1 x 0,35

**Insulation**

Material	Foam polyethylene
Diameter (mm)	1,60
Colour	Natural

**Shield**

Shield	
Material	Tinned copper braid
Coverage	90 %

**Outer sheath**

Material	PVC
Diameter (mm)	2,60
Colour	several

**Printing**

Inscription	Conducfil
-------------	-----------



**COAXIAL/R-02YCY 1x0.35 S**  
**Código - 1948**

**Supply**

Packing	To be defined
---------	---------------

**MECHANICAL CHARACTERISTICS**

Appox. Weight	10,5 Kg/km
Operating temperature range	-20 / +80
Minimum bending radius	52 mm

**ELECTRICAL CHARACTERISTICS**

Conductor DC resistance at 20° C	187 Ohms/km
Shield DC resistance at 20° C	32,8 Ohms/Km
Nominal capacitance	58 pF/m
Nominal impedance	75 ohms
Velocity of propagation	78 %

Attenuation	Frequency (MHz)	dB/100 m
	1	2,1
	5	4,7
	10	7,2
	30	12,3
	100	21,5

Return loss	Frequency (MHz)	dB
	0-800	20
	800-1000	23

Insulation resistance	>5000 Mohms * Km
-----------------------	------------------

Voltage test	1500 v
--------------	--------



**COAXIAL/R-02YCY 1x0.35 S**  
**Código - 1948**

**SAFETY**

**FLAME TEST**

		Compliance
Test for vertical flame spread	IEC-60332-1	<input type="checkbox"/>
Test for vertical flame spread	IEC-60332-2	<input type="checkbox"/>
Test for vertical flame spread	IEC-60332-3	<input type="checkbox"/>
It does not emite toxic fumes or halogens	IEC-754-1	<input type="checkbox"/>
It does not emite corrosive fumes or halogens	IEC-754-2	<input type="checkbox"/>
Low emision of dense fumes	IEC-1034-1	<input type="checkbox"/>

**ENVIRONMENT**

		Compliance
Content of hazardous sustances	Directive 2002/95/CE	<input checked="" type="checkbox"/>

**APPLICABLE SPECIFICATIONS**

		Compliance
Conductor material	UNE-EN 60228	<input checked="" type="checkbox"/>
Insulation material	UNE-EN 50290	<input checked="" type="checkbox"/>