




DIGISON/(AES/EBU)-02Y(St)YY 20x2x0.22 P
Code - 9965



Description

Bare copper conductor. Foam polyethylene insulation. Twisted conductors. Tinned copper drain wire each pair. Aluminium-polyester foil shield each pair. PVC sheath each pair. Lay up pairs. PVC-NBR outer sheath.

PHYSICAL CHARACTERISTICS

Conductor

Material	Bare copper
Section (mm ²)	0,22
AWG	24
Composition	7 x 0,2

Insulation

Material	Foam polyethylene
Diameter (mm)	1,40
Colour	white, red

Twisted

Lay length (mm)	Each 51
-----------------	---------

Individually shield

Drain wire	Tinned copper
Section (mm ²)	0,22
AWG	24
Composition	7 x 0,2
1st Shield	
Material	Aluminium-polyester foil
Coverage	100 %
2nd Shield	NO
Material	
Coverage	



DIGISON/(AES/EBU)-02Y(St)YY 20x2x0.22 P
Code - 9965

Individually outer sheath

Material	PVC
Diameter (mm)	3,7
Colour	Grey

Lay up

Composition	R+7+13 pairs.
-------------	---------------

Outer sheath

Material	PVC-NBR
Diameter (mm)	22,3
Colour	Black

Printing

Inscription	Conducfil
-------------	-----------

Supply

Packing	To be defined
---------	---------------

MECHANICAL CHARACTERISTICS

Appox. Weight	486,2 Kg/km
Operating temperature range	-20 / +80
Minimum bending radius	446 mm

ELECTRICAL CHARACTERISTICS

Conductor DC resistance at 20° C	78,4 Ohms/km
Shield DC resistance at 20° C	78,4 Ohms/Km
Nominal capacitance	40 pF/m
Nominal impedance	110 ohms
Velocity of propagation	78 %
Insulation resistance	>1000 Mohms * Km
Voltage test	1500 v



DIGISON/(AES/EBU)-02Y(St)YY 20x2x0.22 P
Code - 9965

SAFETY

FLAME TEST

		Compliance
Test for vertical flame spread	IEC-60332-1	<input type="checkbox"/>
Test for vertical flame spread	IEC-60332-2	<input type="checkbox"/>
Test for vertical flame spread	IEC-60332-3	<input type="checkbox"/>
It does not emite toxic fumes or halogens	IEC-754-1	<input type="checkbox"/>
It does not emite corrosive fumes or halogens	IEC-754-2	<input type="checkbox"/>
Low emision of dense fumes	IEC-1034-1	<input type="checkbox"/>

ENVIRONMENT

		Compliance
Content of hazardous sustances	Directive 2002/95/CE	<input checked="" type="checkbox"/>

APPLICABLE SPECIFICATIONS

		Compliance
Conductor material	UNE-EN 60228	<input checked="" type="checkbox"/>
Insulation material	UNE-EN 50290	<input checked="" type="checkbox"/>