

Mod. RC 80 F - 100 F Lux Cosmobeam 800 W / 1000 W on yoke

Beside the traditional Cosmobeam, a new range has been designed to meet location's requirements. Its light alloy housing is particularly suitable where lightness and ruggedness are required. High temperature finished it has a properly designed reflector, made of polished aluminium that ensures a high degree of reflectivity. Variable beam luminaire with an extremely smooth and accurate focusing mechanism, allows a particularly even illumination and an excellent power through all the working position. The good ratio weight/power together with a competitive price enable this unit to be ideal in many of our kits. All accessories are fully interchangeable with the traditional Cosmobeam range. It is supplied complete with yoke, 3.5 mt. VDE fire resistant cable and in-line 10 Ah switch protected by a high impact-proof housing.



RC 80 F LUX RC 100 F LUX	,			Ĝî,
<u>⊢ mm. 163</u>	mm. 215	RC 101	accessory holder	350
mm. 270		RC 103	four-leaf barndoor	610
	¥ 🔹	RC 103C	four-leaf barndoor with gel filter clips	625
35 spot 80 floo		RC 103R	four-leaf barndoor with inox wire mesh	635
	50 380	RC 103CR	four-leaf barndoor with inox wire mesh and gel filter clips	650
RC 100 - 1000 W		RC 104	dichroic filter	170
metri 3 35 spot 80 floo	5 7 Ô	RC 105	safety glass	210
	80 300	RC 105 A	diffusion glass	170
RC 80 - 800 W metri 3	5 7	RC 106	scrim set (4 pieces)	150
Box 27 x 21 x h. 17 cm	n. RC 30	RC 107	inox wire mesh (excluding any other accessories)	110
CO Oraciant	Kg. 1,500 RC 100	RC 108	soft light boxes 50 x 50 cm.	580
(Linear tungsten-halogen bulb)		RC 50/55	snoot (front diameter 55 mm.)	200
	- 220 V - 80 mm. V - 220 V - 93 mm.	RC 50/63	snoot (front diameter 63 mm.)	210
			osmoligi	ht