

Mod. RC 910/950 Jambo Par 64


Multiproiettore realizzato in varie versioni da 6 a 24 lampade. Questo modello è particolarmente idoneo per illuminare spazi estesi, laddove la distanza tra luce e soggetto è considerevole, garantendo un flusso luminoso ampio e potente. Utilizza lampade PAR 64 con fascio medio a sezione ellittica, protette da vetro pressato. È possibile variare l'angolazione del campo di luce ruotando i banchi laterali del proiettore. La struttura è realizzata in lamiera di alluminio, materiale robusto e leggero, verniciata ad alta temperatura. Fornito completo di forcella con spinotto 29 mm., paraluce a due sportelli, spina da pannello CEE 63 Ah ed interruttore per ogni lampada. A richiesta è disponibile la rete di proiezione singola.

Mod. RC 910/950 Jambo Par 64


Multilamp luminaire designed for using from 6 to 24 bulbs. This unit is particularly suitable for lighting big spaces, whereas the distance between the source and the subject is considerable, giving a powerful and wide luminous flux. It accepts PAR 64 bulbs with elliptic section medium beam, protected by pressed glass. Beam variation is controlled by pivoting the two outer banks.

It is equipped with stirrup and 29mm. spigot, two-leaf barndoor, 63 Ah panel plug CEE 17 type and a switch for each bulb.

An individual inox wire mesh can be supplied on request.




Paraluce a 2 sportelli (accessorio incluso)
Two-leaf barndoor (accessories included)



RC 951 Rete di protezione singola
single inox wire mesh

Lampada alogena PAR 64 - attacco GX 16d - 3200° K
(PAR 64 tungsten-halogen bulb)




1000W - 220V.

RC 910




mm. 960
mm. 520



RC 920




mm. 990
mm. 740



RC 930




mm. 990
mm. 740



RC 940



mm. 1330
mm. 1080



RC 950



mm. 1330
mm. 1080

