ACCESSORIES(OPTION)

CB-4 50M Intercom Cable









CB-3 20M Intercom Cable

SPECIFICATION

Frequency: 550-3.6KHz, < +/-3dB

THD: < 3%

S/N: > 50dB

Working distance: Up to 200 meter

ITC-100

Tally interface: Two D-Sub 15-PIN terminals

Output: Eight terminals of 5-PIN XLR output Audio Output: : One 3.5mm headphone

One 6.5mm earphone output

One speaker out

General Spec : Power indicator

Microphone on/off switch Intercom select buttons

Mute control

Volume control

DC 12V power indicator

Tally inputs

Full duplex intercom

Dimension: 482mm x 250mm x 44mm

Weight: 1.9 kg

Power : DC 12V/1.5A

Interface: 5-PIN XLR terminal

Audio: One 3.5mm Headphone jack

One 2.5mm Motorola Earphone jack

General Spec: Power indicator

Call button

Intercom between ITC-100SI

Talk button

Volume control

Tally light Red/Yellow output

Tally indicator

Half duplex

Dimension: 113.9mm x 95.4 mm x 35mm

Weight: 350g

Power: Supplied from ITC-100

datavideo

Datavideo Technologies China Co. 2F-D,No.2,Lane777,West Guangzhong Rd, Zhabel District, Shang-hal,China Tel:+86-21-5603 6599

12300-U East Washington Blvd Whittier, CA 90606, Tel:+1-562-696 2324 Fax:+1-562-698 6930

Datavideo Technologies (S) PTE Ltd 100 Lorong 23, Geylang, #01-03 D'Centennial Bldg Singapore 388398 Tel:+65-6749 6866

Californiedreef 26 3565 BL Utrecht, The Netherlands

Datavideo HK Limited

Datavideo UK Limited Unit 2 Waterside Business Glossop, Derbyshire SK13 1BE, UK Tel:+44-1457 851000 Fax:+44-1457 850964

Datavideo Technologies Co., LTD. 10Fl., No.176, Jian-Yi Rd., Chung Ho City, Taipei Hslen Taiwan, 235, Fax:+886-2-8227 2777

☑ D · I · G · I · T · A · L · V · I · D · E · O / P/N:







ITC-100



DESCRIPTION


In the production studio, good communication between the director, cameraman, lighting and control room is essential to produce a polished end result.

The Datavideo ITC-100 Intercom System provides 8-Way talkback and tally indicators. The director can select to talk to an individual channel or to all channels simultaneously. High S/N ratio and full duplex design makes the communication crisp and clear.

The ITC-100 is a standard 19"/1U rack design, so it is easy to integrate into any rack system for using in the field or studio.

FEATURES

- Industry Standard 19"/1U rack design, for easy integration
- Supports 8-Way Intercom (standard package includes 4 sets of ITC-100SL with belt-pack accessories)
- Full Duplex design with additional external earphone and microphone interface
- Two-color Tally light indicator
- Selectable channel talk, broadcast all or mute.
- Half-Duplex design for ITC-100SL to eliminate the environmental noise
- Enables communication between the camera crew
- Communication distance up to 200 meters
- Supplied complete with Gooseneck Microphone and Light



HEADSET SE-800

ITC-100 Intercom Talkback System

The ITC-100 is an intercom talkback system for EFP communication between the director and field cameraman, it supports full duplex talkback and tally indicator, so the director can confidently manage the camera crew in



TALLY

DV



HEADSET



CONNECTION DIAGRAM





The ITC-100 is shipped complete with 4 sets of ITC-100SL; user can order additional ITC-100SL to support up to 8 channels.



Headphone Earphone (Motorola only)

ITC-100SL CONNECTION DIAGRAM



Tally light

TALLY INDICATOR CONNECTION



Amber light means Cued

ACCESSORIES(INCLUDED)



ITC-100SL Belt Packs









INTERCOM





CB-3 20 Meter Intercom Cable (Cascade up to 200 meter)























