

TLM-170GM 17.3" HD/SD TFT LCD Monitor - 1U Foldable Rackmount Tray Unit

- 17.3" (1600x900) LCD TFT Display
- Digital Video Inputs: SD/HD-SDI with loop thru and 2x HDMI
- Digital Audio Inputs: via SDI or HDMI inputs.
- Analogue Video Inputs: Component (Y,Pb,Pr), Composite x2 with loop thru
- Mono Audio Inputs: Single RCA phono socket for analogue inputs.
- Head phone 3.5mm stereo jack socket for discrete audio monitoring.
- Front Panel Buttons allow quick and easy selection of source input as well as PIP, Aspect Ratio, Blue only, Pattern (Colour Bars), Menu and audio controls.
- Colour temperature menu option has 3 modes (6500K, 9300K and user defined)
- OSD audio level peak meter for SDI and HDMI based digital audio inputs.
- On screen overlays for frame marker 80%, 90%, 4:3 marker, 16:9 Marker, Cinema Zone Marker, Center Point, embedded SDI Timecode and Monitor Title.
- 8 Ch-Audio level display & Mute Buttons



(http://www.resource.datavideo.com/images_datavideo/TLM-170GM.jpg)

- Bi-colour Tally light [Red or Amber] and 3.5mm Jack Tally input socket.
- Analogue Audio external speaker outputs L-, L+ and R-, R+ [Max 5v p - p (2w)].
- Supports Pixel Zoom upto 8x
- RJ-45 TCP/IP connection allow s remote set up of the monitor using a PC / Mac based browser.
- USB 2.0 port for easy update of firmware