



DMON-12S

12 Channel Multiviewer
with SDI and HDMI OUTPUTS for 3G/HD/SD

PRODUCT FEATURES

- Low cost miniature (3G/HD/SD)-SDI 12 to 1 Multiviewer or 12 to 1 input multiplexer
- Various multiviewer layouts
- Selectable output format in Multiviewer mode
- Low latency buffering for each input allowing non-synchronous inputs
- Linked (3G/HD/SD)-SDI and HDMI outputs
- 12 x (3G/HD/SD)-SDI inputs with auto detection (26 Formats supported in total)
- Each quadrant is independent of the others, allowing any 3G/HD/SD format of any frame rate to be displayed simultaneously
- Variable aspect ratios per quadrant
- In Pass-Through mode the selected input is passed through to both the (3G/HD/SD)-SDI and HDMI outputs
- The DMON-12S is a truly portable converter, that incorporates our new easy to use LCD and button control system. This gives you easy access to all of the amazing features without using complicated LED/button control, dip switches or having to carry around a computer to change a simple setting.
- This unit also includes:
 - 32 GPI
 - USB port for control and firmware updates
 - Heavy duty metal box
 - Metal Thread Locking DC Power Socket
 - Power Supply, HDMI Cable and USB Cable

TVTechnology



PRELIMINARY SPECIFICATIONS

SDI INPUT & OUTPUT FORMATS	3G: SMPTE 424M@2.97 and 2.967Gb/s • 1080p@60/59.94/50Hz HD: SMPTE 292M/274M/296M@1.485 and 1.435Gb/s • 1080i@60/59.94/50Hz • 1080p/psf@30/29.97/25/24/23.98Hz • 720p@60/59.94/50/30/29.97/25/24/23.98Hz SD: SMPTE 259M@270Mb/s • 625i50 • 525i59.94	LCD / BUTTON MENU OPTIONS	• HDMI output type • Multiviewer layout • Multiviewer or source selection • Multiviewer output format selection • Multiviewer output aspect and type of 16:9 or 4:3 at either 90 or 100% of screen size • Multiviewer individual aspect format for each input of Same as output, Letter-box or Pillar-box • Multiviewer mode reference
HDMI OUTPUT FORMATS	• 1080p@60/59.94/50Hz • 1080i@60/59.94/50Hz • 1080p@30/29.97/25/24/23.98Hz • 720p@60/59.94/50/30/29.97/25 • 625i50 • 525i59.94	INPUTS	• 12 x (3G/HD/SD)-SDI • Input Equalization > 100M using Belden 1694A • USB for control and updates
LED STATUS	• Power • 12 x Signal lock and rate	OUTPUTS	• HDMI Type A • 2 x SDI (3G/HD/SD)-SDI
POWER	• +5V to +32V DC • Positive Centre Pin	DIMENSIONS	220mm x 103.7mm x 29.5mm (8.7" x 4.1" x 1.2")

DISTRIBUTED BY:

www.decimator.com

Innovative Monitoring Solutions

Copyright © 2014 DECIMATOR DESIGN PTY LTD DMON-12S BROCHURE V1.0