

HD/SD Chroma Keyer

MBP-100CK

The MBP-100CK is a High performance chroma keyer with FOR-A's unique algorithm.



- 4:4:4:4 Internal Process
- HD/SD-SDI 3 inputs, 8 outputs
- Edge color replacement
- Filtering to eliminate flickering
- Internal Delay Lines (7 frames)
- 2 Independent Layering Downstream Keyers
- Still Store Function
- GUI Control Software
- MBP-12RU: Remote control unit (option)



MBP-100CK Set-up Display




Chroma Key Display


Specifications

Standard	HD: 1080/59.94i, 1080/50i, 720/59.94p, 720/50p SD: 525/60 (NTSC), 625/50 (PAL)
Standard (Option)	1080/30p, 1080/30PsF, 1080/29.97p, 1080/29.97PsF, 1080/24p, 1080/24PsF, 1080/23.98p, 1080/23.98PsF
Video Input	HD-SDI: 1.485/1.001Gbps or SD-SDI: 270Mbps, 75Ω, 3 inputs (CAMERA, CGV, CGK), BNC
Reference Input	BB: NTSC: 0.429Vp-p/PAL: 0.45Vp-p or Tri-level sync: 0.6Vp-p, 75Ω, 1 input, BNC
Video Output	
OUTPUT (V1-V4)	HD-SDI: 1.485/1.001Gbps or SD-SDI: 270Mbps, 75Ω, 4 outputs, BNC
OUTPUT 2 (V1-V4) (Same signals as OUTPUT)	HD-SDI: 1.485/1.001Gbps or SD-SDI: 270Mbps, 75Ω, 4 outputs, BNC
VGA Output	15-pin D-sub (female), 1 output.
Signal Processing	4:4:4:4 component
Quantization	Y: 10-bit, C: 10-bit, K: 10-bit
Chroma Keyer	FOR-A unique algorithm chroma keyer with Auto chroma key and Edge color replacement technology
DSK	MIX: Normal/Add (selectable) Priority: Selectable 4 layer Transition Rate: 0 sec - 30 sec
Camera Delay Adjustment	0H - 7 frame
Interfaces	VGA: 15-pin Mini D-sub (female), 1ea. Ethernet: 100Base-TX (1000Base-T is future support), RJ-45, 2 ea. USB: USB 2.0 (High Speed) Series A connector, 4ea. (2 ports on front panel and 2 ports on rear panel) REMOTE (RS-422): 9-pin D-sub (female), 1ea. RS-232C: 9-pin D-sub (male), 1ea. GPI/ALARM: 15-pin D-sub (female), 1ea. - GPI: 4 inputs/2 outputs (relay input, open collector output) - ALARM: Power, Fan alarms (relay output)
Temperature / Humidity	10°C - 40°C / 30% - 90% (no condensation)
Power / Consumption	100VAC - 240VAC, 50/60Hz / Approx. 115W
Dimensions / Weight	430 (W) x 44 (H) x 500 (D) mm EIA1RU / Approx. 9kg
Accessories	Operation manual, AC cord, rack mount brackets
Options	MBP-12RU: Remote control unit

Rear Panel



External Dimensions



Remote Control Unit: MBP-12RU



Remote control unit enabling control over the MBP-100CK. It provides intuitive operation by touch panel and button switch.

FOR-A COMPANY LIMITED

Head Office : 3-8-1 Ebisu, Shibuya-ku, Tokyo 150-0013, Japan

FOR-A America Corporate Office : 11125 Knott Ave., Suite #A, Cypress, CA 90630, USA

FOR-A America East Coast Office : 2 Executive Drive, Suite 670, Fort Lee Executive Park, Fort Lee NJ 07024, USA

FOR-A America Distribution & Service Center : 2400 N.E. Waldo Road, Gainesville, FL 32609, USA

FOR-A Latin America & the Caribbean : 5200 Blue Lagoon Drive, Suite #760, Miami, FL 33126, USA

FOR-A Corporation of Canada : 346A Queen Steet West, Toronto, Ontario M5V 2A2, CANADA

FOR-A UK Limited : UNIT C71, Barwell Business Park, Leatherhead Road, Chessington Surrey, KT9 2NY, UK

FOR-A Italia S.r.l. : Viale Europa 50 20093, Cologno Monzese (MI), Milan, Italy

FOR-A Corporation of Korea : 801 Dongsan Bld., 53-1 Dongsan-Dong, Youngdeungpo-Gu, Seoul 150-800, Korea

FOR-A China Limited : 708B Huateng Building, No. 302, 3 District, Jinsong, Chaoyang, Beijing 100021, China

Homepage: <http://www.for-a.com/>

+81 (0)3-3446-3936

Fax : +81 (0)3-3446-1470

+1 714-894-3311

Fax : +1 714-894-5399

+1 201-944-1120

Fax : +1 201-944-1132

+1 352-371-1505

Fax : +1 352-378-5320

+1 305-931-1700

Fax : +1 305-264-7890

+1 416-977-0343

Fax : +1 416-977-0657

+44 (0)20-8391-7979

Fax : +44 (0)20-8391-7978

+39 02-254-3635/6

Fax : +39 02-254-0477

+82 (0)2-2637-0761

Fax : +82 (0)2-2637-0760

+86 (0)10-8721-6023

Fax : +86 (0)10-8721-6033



JQA-QM4231



JQA-EM4853