



|                           |   |     |     |     |     |
|---------------------------|---|-----|-----|-----|-----|
| Applicable camera (model) | 1 | 2/3 | 1/2 | 1/3 | 1/4 |
|---------------------------|---|-----|-----|-----|-----|

- 360° view eliminates blind spots
- Optimized design for VGA to 2 Megapixel sensors both analog and IP cameras
- Standard CS Metal Mount for 1/3" sensors
- Equipped with 3 axes sensor centering adjustment
- ImmerVision Enables® SDK available for DVR/NVR/VMS integration
- Patented panomorph optical technology



| Applicable to 1/3                       |       | YF360A-2                             | Applicable to 1/3                    | YF360A-SA2 |
|-----------------------------------------|-------|--------------------------------------|--------------------------------------|------------|
| Focal length in mm                      |       | 0.9 (short axis) / 1.15 (long axis)  | 0.9 (short axis) / 1.15 (long axis)  |            |
| Iris range                              |       | F1.9 (short axis) / F2.4 (long axis) | F1.9 (short axis) / F2.4 (long axis) |            |
| Operation                               | Focus | manual                               | manual                               |            |
|                                         | Iris  | none (open iris)                     | Auto (DC type) *                     |            |
| Angle of view ( H x V )                 |       | 182° x 182°                          | 182° x 182°                          |            |
| Anamorphic ratio                        |       | 1.3 (4:3)                            | 1.3 (4:3)                            |            |
| Focusing range (from front of the lens) |       | infinity ~ 20 mm                     | infinity ~ 20 mm                     |            |
| Mount                                   |       | CS                                   | CS                                   |            |
| Mass in g                               |       | 180                                  | 180                                  |            |
| Remarks                                 |       | ImmerVision Enables<br>RPL A0NKV     |                                      |            |

\*1: The iris automatically closes when the camera is turned off.