

# TL-V3100 Digital Conference System



**GONSIN TL-V3100 digital conference system offers a multifunctional conferencing solution featuring microphone discussion, video tracking, audiovisual recording and software control.**

## Chairman Unit / Delegate Unit

The conference unit allows the delegate to speak, request to speak and listen to speech. Each unit comes with headphone jack and volume control for the delegate to listen to the floor audio, and adjust volume level for comfortable listening. Built-in speaker automatically mutes when microphone is turned on. 1 to 4 delegate microphones can be active at the same time. Multiple chairman and vice-chairman units can be used in one system, and can be active at any time regardless of preset delegate mic limit. Chairman unit has the additional priority button to override all delegate units to control the conference.

## Main Features

- ◆ Highly resistant to mobile phone interference
- ◆ Long microphone pick-up range
- ◆ High quality built-in loudspeaker
- ◆ Red ring luminant to indicate active mic

## Basic Functions

- ◆ Microphone discussion: push to talk or request to talk. Floor audio listening via headphone or built-in loudspeaker with volume control. AUTO / FIFO / OPERATOR modes are available for microphone management.
- ◆ Supports automatic video tracking, with preset panoramic position



## Technical Specifications

|                          |                            |                        |                       |
|--------------------------|----------------------------|------------------------|-----------------------|
| Mounting type            | fixed or portable tabletop | Power consumption      | 2W                    |
| Microphone pick-up range | up to 600 mm               | Microphone stem length | 410 mm                |
| Frequency response       | 50Hz-18kHz                 | Headphone jack         | mini 3.5mm            |
| S/N ratio                | -95dB/1mV                  | Internal loudspeaker   | 8Ω/2W                 |
| Sensibility              | -46dB±4dB                  | Dimensions             | 135×150×50 mm (W*D*H) |
| Power input              | 24V DC                     | Weight                 | 0.75 kg               |

## System Configuration

