

IFD2115

Featherweight Kit w/ 2x IFD1024 & 1x IFD576
w/ AB to V-Mount Adapter Plate

ONE SHEET

Overview

The 3-Point Light Kit features include 5600K daylight capabilities and a 50-degree angle that delivers reliable, consistent performance.

The IFD1024 Featherweight Daylight LED and the IFD576 Featherweight Daylight LED Light features energy efficient LED lights that are dimmable in 1 step increments from 10-100% using the LCD touchscreen. A large rotary knob and an included remote are also used for dimming. The compact design with integrated yoke mount makes both the IFD1024 and IFD576 portable and easy to set up. A multi-voltage power supply is included and for portable power pro battery plates for both Sony V-mount and Anton Bauer are supplied. A removable diffuser is included and the pre-mounted four leaf barn doors with intensifiers can be folded flat for transportation.



IFD2115 | Kit w/ 2x IFD1024 & 1x IFD576 w/ AB to V-Mount Adapter | UPC Code: 847983013623

Special Features

- Color Temperature of 5600K
- (2) IFD1024 + (1) IFD576 Fixtures with Stands and Bags
- Ultra-Light, Compact, & Easy to Set-up Daylight LED
- LCD Touch-Screen Controller and Dimmer Knobs
- Includes Pro Battery Plate for Anton Bauer & Sony V Mount
- Includes Yoke Mount, Barn Doors with Intensifiers, and Diffuser

Recommended For

- Studio Lighting
- Product Photography



www.facebook.com/ikanseit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

IFD2115

Features you need, Prices you want.

Specifications

Beam Angle	50°
Build Material	Heavy Duty Plastic
Control	Local Knob
Cooling System	Passive Cooling
Dimming	10-100%
Fixture Weight	4 lbs & 6 lbs
Focusing	NO
Head Type	Daylight (5600K)
Lens	60° Lens
Mount	Yoke
Power Supply	12v @ 3.33 Amps & 12v @ 6.66 Amps
Rating	120v @ 60Hz
Shipping Weight	30 lbs

What's Included

- 1 x IFD576 Light
- 1 x Light Kit Bag
- 1 x Stand Bag
- 2 x IFD1024 Lights
- 3 x AB Battery Plates (Attached)
- 3 x AB to V-Mount Adapter Plates
- 3 x Heavy Duty Light Stands

Specifications for IFD576

Operating Volts	12-24v
Operating Wattage	120v/60Hz: 46watts
Beam Angle	50°
Foot Candles	520.6
Color Temperature	5600K (±100)
Brightness	3' / 5602 lux / 5600K (±100)
Light Source	576 0.06watt LED @ 5600K
Fixture Size	14" x 8.5" x 2.75"

Specifications for IFD1024

Operating Volts	12-24v
Operating Wattage	120v/60Hz: 82 watts
Beam Angle	50°
Foot Candles	979.8
Color Temperature	5600K (±100K)
Brightness	3' / 10543 lux (±100K) / 5600K (±100K)
Light Source	1024 0.06 watt LED @ 5600K
Fixture Size	14" x 14" x 2.75"

Optional Accessories

- AB101** Anton/Bauer Power Tap Cable w/ Coaxial
- AB102** Anton/Bauer Power Tap Cable w/ 4-Pin XLR

Photometrics

