

Blitz 400 Wireless Video Receiver

Model: BZ400-RCV

Features

- Spare Receiver Compatible with Blitz 400 Syst
- Up to 4 Receivers can be used with 1 transmitt
- 3G-SDI and HDMI Inputs and Outputs
- Designed with Ikan's Quick Mount System
- Supports Sony L Series Batteries



	Transmitter	Receiver
Interface	3G-SDI Input (BNC Female) HDMI Input (Type A Female) 2 x Antenna Ports (RF-2 SMA Male) DC Input (4 pin LEMO Female)	3G-SDI Output (BNC Female) HDMI Output (Type A Female) DC Input (4 pin LEMO Female)
Input Voltage	7 - 36V DC	7 - 36V DC
Power Consumption	<6.5W	<6.5W
Dimensions	115 x 67 x 23 mm	152 x 95 x 23 mm
Weight	270g	355g
Input Video Format	HDMI: 525i, 625i, 720p 50/59.94/60, 1080i 50/59.94, 1080p 23.98/24/25/29.97/30/50 /59.94/60 SDI: 3G, HD, and SD-SDI (Auto Selected) SMPTE-259/274/292/296/372/424/425	HDMI: 525i, 625i, 720p 50/59.94/60, 1080i 50/59.94, 1080p 23.98/24/25/29.97/30/50 /59.94/60 SDI: 3G, HD, and SD-SDI (Auto Selected) SMPTE-259/274/292/296/372/424/425
Output Video Format		
Input Audio Format	SDI Embedded 4 Channel 24-bit / 48KHz	SDI Embedded 4 Channel 24-bit / 48KHz
Audio Output		SDI Embedded 4 Channel 24-bit / 48KHz
Signal Indicators	Power: Green / Video: Yellow	Power: Green / Wireless Signal 5 x Green Video: Yellow
Frequency Bands	5.1 - 5.9 GHz	5.1 - 5.9 GHz
Modulation Mode	OFDM 16QAM	OFDM 16QAM
Transmission Power	Max 21 dBm	
Receiver Sensitivity		-75 dBm
Band	40MHz	40MHz
Operating Temperature	0°C ~ 40°C (Operating) -20°C ~ 60°C (Storage)	0°C ~ 40°C (Operating) -20°C ~ 60°C (Storage)
Compliance	FCC, CE	FCC, CE

WHAT'S INCLUDED:

1 X Articulating Arm
1 X BZ400 Receiver
1 X Clamp
1 X P-TAP To LEMO Compatible Cable

SPECIFICATIONS:

Shipping Dimensions: 8 x 5.5 x 2.5 in.
Shipping Dimensions (Metric): 20.3 x 13.9 x 6.3 cm
Shipping Weight: 1 lbs
Shipping Weight (Metric): 0.5 kg
UPC Code: 847983020638