

OYB5-3PT-KIT

Onyx Half x 1 Bi-Color 3-Point LED Light Kit

ONE SHEET

Overview

The Onyx Half x 1 Bi-Color Aluminum LED Light is fitted with 900 high-quality LED Lights. The aviation-grade aluminum panel design allows for better heat ventilation. The OYB5 provides a flicker-free experience when adjusting the brightness (10-99%) and color temperature (3200K-5600K). The OYB5 can be controlled remotely with either the included remote control or DMX via the Ethernet port. Having the option of being powered either by the power adapter or two Sony “L” series style batteries, the OYB5 can meet both your studio or field needs.



OYB5-3PT-KIT | Onyx Half x 1 Bi-Color 3-Point LED Light Kit | **UPC Code:** 847983022434

Special Features

- Durable lightweight aluminum frame
- Bi-Color Adjustable from 3200K-5600K
- DMX Ethernet and wireless remote control

Recommended For

- Field and Studio Use

OYB5-3PT-KIT

Aluminum Frame

The Onyx Half x 1 LED Light's aluminum body gives it a perfect balance of being both durable and lightweight. The light fixture gives off minimal heat due to the aluminum frame which allows for excellent ventilation.

96+ CRI LEDs

With 900 96+ CRI LEDs, the Onyx OYB5 light provides incredible color rendition and brightness. The Onyx OYB5 LED Light features a bi-color adjustable range between 3200K-5600K.

Remote Controlled

You can easily control the light up to 150 feet away with the remote control. In addition, you can control multiple lights at the press of a button. DMX Control is also available through the Ethernet ports.

Battery Powered

The Onyx Half x 1 can be powered either by the included AC power supply or by two Sony "L" Series style batteries.

What's Included

- 1 x Light Bag
- 1 x Stand Bag
- 3 x Barn Doors
- 3 x Compact Light Stand
- 3 x Dual Battery Charger
- 3 x OYB5 Light Fixture
- 3 x Power Adapter
- 3 x Remote Control
- 3 x Yoke
- 3 x Batteries

Features you need, Prices you want.

OYB5 Specifications

Color Temperature	3200K-5600K
Dimming	10%-99%
DMX Standard	DMX512 (Ethernet Interface)
Fixture Size	16 x 16 x 1.75 in.
Fixture Weight	5 lbs
Remote Control	99 Channels 2.4G Wireless Remote Control

Shipping Specifications

Shipping Dimensions	24 x 22 x 18 in.
Shipping Weight	52 lbs

Optional Accessories

HD-STND-V2	Heavy Duty Light Stand
IB-L130S	V-Mount Professional Battery
PWRGP-01	Power Grip
CP-STND-V3	Compact Light Stand Version 3
KCP-703	Stage Clamp 1/ 16mm Stud
ROLLR-STND10	2-Stage Roller Stand 10 ft 6 in
SW-04	Safety Wire