

OYB5

Onyx Half x 1 Bi-Color Aluminum LED Light

ONE SHEET

Overview

The Onyx Half x 1 Bi-Color Aluminum LED Light is fitted with 900 High-Quality LED Lights. The aviation grade aluminum panel design allows for better heat ventilation. The OYB5 provides a flicker-free experience when adjusting the brightness (10-99%) and color temperature (3200K-5600K). The OYB5 can be controlled remotely with either the included remote control or DMX via the Ethernet port. Having the option of being powered either by the power adapter or two Sony "L" series style batteries, the OYB5 can meet both your studio or in-the-field needs.



OYB5 | Onyx Half x 1 Bi-Color Aluminum LED Light | UPC Code: 847983021871

Special Features

- Durable Lightweight Aluminum Frame
- Bi-Color Adjustable from 3200K-5600K
- 96+ CRI LEDs
- DMX Ethernet and Wireless Remote Control
- Battery-Powered by two Sony "L" Series Style Batteries

Recommended For

•



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

OYB5

Aluminum Frame

The Onyx Half x 1 LED Light's aluminum body gives it a perfect balance of being both durable and lightweight. The light fixture gives off minimal heat due to the aluminum frame which allows for excellent ventilation.

96+ CRI LEDs

With 900 96+ CRI LEDs, the Onyx OYB5 light provides incredible color rendition and brightness. The Onyx OYB5 LED Light features a bi-color adjustable range between 3200K-5600K.

Remote Controlled

You can easily control the light up to 150 feet away with the remote control. In addition, you can control multiple lights at the press of a button. DMX Control is also available through the Ethernet ports.

Battery Powered

The Onyx Half x 1 can be powered either by the included AC power supply or by two Sony "L" Series style batteries.

What's Included

1 x Barn Doors
1 x Dual Battery Charger
1 x Light Bag
1 x OYB5 Light Fixture
1 x Power Adapter
1 x Power Cord
1 x Yoke
2 x Batteries

Features you need, Prices you want.

Specs 1

| | |
|-------------------|---|
| Battery Type | Sony "L" Series Style Batteries |
| Color Temperature | 3200K-5600K |
| Dimming | 10%-99% |
| DMX Standard | DMX512 (Ethernet Interface) |
| Fixture Size | 14.5 x 11 x 1.75 In. |
| Fixture Weight | 4 lbs |
| Remote Control | 99 Channels 2.4G Wireless Remote Control |

Shipping Specifications

| | |
|---------------------|-----------------------|
| Shipping Dimensions | 15.7 x 11.8 x 5.5 In. |
| Shipping Weight | 7 lbs |

Optional Accessories

| | |
|--------------|--|
| CP-STND-V3 | Compact Light Stand Version 3 |
| HD-STND-V2 | Heavy Duty Light Stand |
| KCP-703 | Stage Clamp w/ 16mm Stud |
| ROLLR-STND10 | 2-Stage Roller Stand 10ft 6in |
| SW-02 | Safety Cable Wire 23.5" (600mm x 2mm) w/ Carabiner |
| DV-DUAL-S550 | DV Camera Battery Kit (2x Sony NP-F550 2900mah Replacement Lithium Batteries & Dual Battery Charger) |
| DV-DUAL-S750 | DV Camera Battery Kit (2x Sony NP-F750 5800mah Replacement Lithium Batteries & Dual Battery Charger) |
| DV-DUAL-S970 | DV Camera Battery Kit (2x Sony NP-F970 6600mah Replacement Lithium Batteries & Dual Battery Charger) |

ikan

Houston, Texas

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

