

GM SERIES

42"/47"/52"


1920 x 1080 Full HD LCD Monitor

GM-F420S GM-F470S GM-F520S

*Superior full HD picture performance,
stylish super-thin bezel design, with high reliability*



GM-F420S



GM-F470S



GM-F520S

■ Features

Extended Line up of 3 sizes for varying applications

- 3 sizes of 42/47/52 - inches

Excellent Picture Quality & Performance

- Native Full HD 1920x1080 pixels resolution
- Panel brightness of 700 cd/m² highly visible even under outdoor ambient lighting
- Wide viewing angle, up to 178 degree (vertical/horizontal)

Functional & Stylish Design

- Ultra-slim bezel of 15mm width (GM-F420S/GM-F470S) and 17mm width (GM-F520S) permits Video Wall application
- Also vertically positionable


High Reliability

- Continuous operations 24 hours/7 Days a week
- Full metal cabinet using light-weight aluminum

Comprehensive System Connectivity & Networking

- "LAN Remote" allows off-site control & monitoring via network PC
- Professional connectivity; RS-232C, MAKE/TRIGGER, RS-485
- Flexible installation (multiple mounting points)
- When detecting a person, "Motion sensor" feature automatically switches functions for timely information display
- A/C outlet provides power for additional device JVC recommend (eg. PC)
- Rear space for integrating system unit (eg. PC; set-top box)
- Multi-screen, Video Wall use (1x2 to 5, 2 to 5x1,2x2 upto 5x5 Tile Matrix capable)
- VESA wall mount compatible

■ Motion sensor




The "Motion sensor", a JVC Original Innovation designed specifically for Digital Signage and Point-of-Sales applications, triggers pre-programmed functions to display timely information such as promotional messages to the viewers.


- Detectable distance: up to 5m (max.)
- Detectable angle: 80 degree horizontally and 80 degree vertically
- Continuous detection until the viewer stops moving or steps out of range.
- The "Motion sensor" can be setup on the top or bottom of the LCD.

■ Mechanical Feature

Front



Rear




■ Specifications

Model		GM-F420S	GM-F470S	GM-F520S
Type		42 inch LCD monitor	47 inch LCD monitor	52 inch LCD monitor
LCD Panel		TFT Active Matrix		
Screen Size		42 inch	47 inch	52 inch
Aspect Ratio		16:9		
Pixel Number		1920 x 1080		
Brightness		700 cd/m²		
Viewing Angle		89/89/89/89		
Contrast Ratio		1000:1		2000:1
Response Time (G to G)		9 msec		8 msec
Display colour		1.07 billion (10-bit)		16.7 million (8-bit)
Signal Format	Video	NTSC / PAL / SECAM / PAL-M / PAL-N		
	RGB	VGA-FHD (1920 x 1080)		
	DVI (HDCP)	VGA-FHD (1920 x 1080) 60 Hz		
Dimensions (W x H x D)		963.6 x 556.6 x 151.2 mm (38 x 22 x 6 inches)	1075.2 x 620.4 x 151.2mm (42-3/8 x 24-1/2 x 6 inches)	1199.2 x 695.2 x 161.5 mm (47-1/4 x 27-3/8 x 6-3/8 inches)
Bezel		15 mm		17 mm
Operating Temperature		0°C to 40°C (32°F to 104°F)*		
Storage Temperature		-20°C to 60°C (-4°F to 140°F)		
Power Requirements		AC 120 / 220 - 240 V		
Weight		24.9 Kg (54.8 lbs)	29.8 Kg (65.6 lbs)	40 Kg (88 lbs)
Frequency		50 Hz / 60 Hz		
Speaker		1.7 W + 1.7 W		
Ext. Speaker Connector		2.3W + 2.3W		
Accessories		AC power cord, Power cord holder, Remote control, Motion sensor, Stand		
Input/Output Terminals				
Video		BNC x 1, with bridge out D-sub (15-pin) x 1 (DDC2B)		
PC	RGB input	D-sub (15-pin) x 1 (Active output)		
	RGB output	DVI-D x 1 (DDC2B)		
Audio	DVI input	RCA x 2 (L / R), 500 mV (rms) with bridge out		
	Audio 1 * Selectable for each Video and PC input	Stereo Mini Jack x 1, 500mV (rms) with bridge out		
	Audio 2 * Selectable for each Video and PC input	Speaker output terminal (L / R)		
External Control	Audio out	D-sub (9-pin) x 1		
	RS-232C	RJ-45 x 1 (8-pin)		
	RS-485 / MAKE / TRIGGER IN	RJ-45 x 1 (8-pin)		
	RS-485/IR OUT	RJ-45 x 1 (8-pin)		
	LAN Remote	RJ-45 x 1 (8-pin)		


*GM-F520S is tentative. E & O E. Design and specifications subject to change without notice.

■ Dimensions


GM-F420S



GM-F470S



GM-F520S




■ Input/Output Terminal 1




■ Control Terminal




■ Input/Output Terminal 2



■ Input/Output Terminal 3



Provided Accessories



All pictures are simulated.

INPUT TERMINALS	DVI-D
	Audio In/Out
	Speaker Stereo
CONTROLS	RS-232C
	LAN Remote
	Remote Control
	RS-485 In/Out
FUNCTIONS	Make/Trigger
	Native HD 1920 x 1080
	High Brightness 700 cd/m ²
	Motion Sensor
	PIP/PBP
	24-hour 7 days operation
	Picture mode
INSTALLATION	CTI/LTI
	Slim bezel 15 mm (for GM-F420S/F470S) 17 mm (for GM-F520S)
	VESA
OPERATION	Power AC