

JVC

FULL HD NETWORK CAMERA SERIES

VN-H137BU

VN-H237BU

VN-H257VPBU

SuperLoLux^{HD}™

Special renewal for more versatile installation

- Built –in upgraded SLL HD lens for VN-H137BU and VN-H237BU
- KA-ZH215U heater option enables -30 deg. C installation of VN-H257VPBU Outdoor vandal dome
- “Best of Best” settings enables SLL HD amazing day/night performance and colour reproduction
- 25/25 fps dual distribution (720p+VGA or 1080p + VGA)

VN-H237U IK10 vandal resistant mini dome



VN-H257VPBU IP66+ Super vandal proof outdoor dome



VN-H137U lens integrated box camera



Optional heater unit for -30 deg.C installation [VN-H257VPBU]

NEW PRODUCT NEWS

■ Specifications

		VN-H137BU	VN-H237BU	VN-H257VPBU
Camera and Lens	Image device	Super LoLux CMOS, 1080p 2.2 megapixel		
	Minimum. Illumination (25%, AGC HIGH)	Colour: 0.15 lx B&W : 0.1 lx		Colour: 0.15 lx B&W : 0.025 lx
	Lens	3.0-9.0 mm 3x vari-focal, F1.2		
	Day/Night	Easy D/N		True D/N
	Wide Dynamic Range	C.L.V.I. (Clear logic video intelligence)		
	3D Noise reduction	3DNR		
	White balance	Manual/ATW-Wide/ATW-Narrow/AWC		
	Sens-up	Off, x2 to x60		
	BLC	4 patterns		
	Programable scene file	8 settings		
	Motion detect	Precise motion detection, tamper detection		
	Privacy mask	Yes		
	Focus adjustment	Manual		Remote/Auto
	Fine focus adjustment	Yes		
Network	Picture resolution	H.264HP/H.264MP/JPEG 1920x1080, 1280x960, 1280x720, 640x480, 640x360, 320x240 MPEG4 640x480, 320x240		
	Stream pattern examples	Single: 1080p@30fps/H.264 or 1080p@15fps/JPEG Dual: 1080p@25fps/H.264 + 640x360@25fps/H.264, 1080p@15fps/H.264 + 1080p@15fps/JPEG Triple: 1080p@15fps/H.264 + 1080p@15fps/H.264 + 640x360@15fps/H.264		
	Protocol	TCP/IP, UDP/IP, FTP, ICMP, ARP, DHCP, SNTP, HTTP, DSCP, SMTP, RTP, RTSP, IGMP, IPv6, HTTPS, SNMP, AMX Device discovery, ONVIF		
	Web viewing PC	Core2Duo, 2GB memory, Windows Vista Business(SP2)/Windows XP Pro (SP3)/Windows 7 Pro, IE8/9		
General	Local recording	SDHC		
	Audio communication	-		Yes (In/Out) mu-low
	Alarm	-		In x 2 / Out x 2
	Dust/water protection	-		IP66
	Vandal protection	-	IK10 rated Vandal resistant [20J]	Vandal proof [50J]
	Power	PoE		PoE, 24VAC
	Power consumption	120 mA (PoE)		150mA (PoE) 1.28A (24VAC with heater)
	Temperature range	-10 to 50 deg/C		-10 to 50 deg/C -30 to 50 deg/C with heater
	Dimensions (WxHxD)	55 x 61 x 170 mm	Dia. 111 x H117 mm	
	Weight Approx	390 g	450 g	1.3 kg
	Option	-		Heater unit KA-ZH215U

Specifications subject to change without notice.

Copyright 2012 JVCKENWOOD Corporation All rights reserved.

All product names stated in this document are trademarks or registered trademarks of their respective companies.

Marks such as TM, ®, and © are omitted in this document.