



Model No.:KVM-2450W

Display Size:24"

Resolution:1920x1200

Aspect Ratio:16 : 10

Introduction:Full HD 24" LCD Monitor,support 3G/H SDI, PIP/PBP for 2 SDI,excellent features waveform vectorscope, Histogram,UMD,Picture flip, Pixel measure,Focus...

KVM-2450W a 24" high performance LCD monitor offers native 1920 x 1200 full HD resolution,supports full video formats including 3Gbs SDI 4: 4: 4 12Bit signals and professional features.True color processing with full broadcasting functions such as vaverform,histogram,pixel measure and range erro ,and more functionality, at a price that fits your budget.

Product Highlight

- **24" 1920×1200** native resolution,IPS LCD panel
- **900 Nits High Brightness**
- 12Bit video processing
- 3D LUT color calibrated via Lightspace or Calman
- 3G-SDI 4:4:4 12Bit signals (SMPTE 425M A/B)
- 2x2K/3G/HD-SDI in/out
- Composite/Component in/out
- PIP/PBP(size/position adjustable)
- Wide type/Waveform(waveform alarm)
- *Waveform, Vectorscope, Audio Meter for SDI1, SDI2*
- *Waveform, Vectorscope, Audio Meter for HMDI*

- Histogram
- Pixel Measurement (Y/R/G/B Values Comparision)
- Audio Phase
- Picture Flip,H/V Delay
- Focus Assist,Zoom
- False Color,Zebra
- Scan,Marker,Blue Only/Mono
- Time Code
- Fast mode(minimize the delay time,interlace scan without converting into progressive scan)
- Audio Meter in horizontal and vertical (16ch SDI,2ch HMDI)
- Dynamic UMD(TSL3.1/4.0)
- Power-off Memory
- Ethernet/GPI
- RS422 in/out

Specifications

LCD	
Display Size	24"
High Resolution	Full HD 1920×1200
Aspect Ratio	16 : 10
Wide Viewing Angle	178°(H) / 178°(V)
Pixel Pitch	0.270×0.270(mm)
Color Depth	1.07B
Back Light	LED
Brightness	900cd/m2
Contrast Ratio	1000:1

Input

2 × BNC	SDI1/2 Channel Input (3G/HD/SD-SDI Auto-Detected)
----------------	--

3 × BNC	YPbPr/Video/Y/C
1 × HDMI	Support
1 × DVI/VGA	DVI-I Input

Output

2 × BNC	SDI1/2 Channel Output (3G/HD/SD-SDI Auto-Detected)
3 × BNC	YPbPr/Video/Y/C

Compatible SDI Formats

SMPTE-425M-A/B	4:2:2 YCbCr 10-bit	1080p(50/59.94/60)
	4:4:4 YCbCr/RGB 10-bit	1080i(60/59.94/50)
	4:4:4 YCbCr/RGB 12-bit	1080p(30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
	4:2:2 YCbCr 12-bit	1080i(60/59.94/50)
		1080p(30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
	4:4:4 YCbCr/RGB 10-bit	720p(60/59.94/50/30/29/25/24/23.98)
SMPTE-274M	1080i(60/59.94/50)	
	1080p(30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)	
SMPTE-296M	720p(60/59.94/50/30/29/25/24/23.98)	
SMPTE-260M	1035i(60/59.94)	
SMPTE-125M	480i(59.94)	
ITU – R BT.656	576i(50)	

Audio In / Out

SDI Audio In	16 Channel Embedded Audio
Audio Meter Display(VU+PPM)	H/V Audio Level Meter Display
Analog Audio Input	3.5mm Headset Switch Cable
Audio Headset Output	3.5mm Headset Jack
Built-in Speaker	2.5W×2

General

Operating Temperature	-10°C~50°C
Input Voltage	AC 100-240V 50/60Hz ; DC 12V
Power Consumption	65W
Power-Saving Mode	Turn off unimportant Key Automatically if No Signal Input
Shell Materials	Aluminum on Front-Shell/Base Supporter/Rust-Proof iron on Back-Shell
Accessory	Power Cord /Desktop stand
Optional	Wall-Mount VESA bracket