

105A

1:5 Stereo Audio Distribution Amplifier





The 105A is a high-performance distribution amplifier for unbalanced stereo audio signals. It takes one stereo input and distributes the signal to five identical stereo outputs.

FEATURES

- Level (Gain) Controls.
- S/N Ratio 80dB (unweighted).
- Compact Kramer TOOLS™ 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.

TECHNICAL SPECIFICATIONS

INPUT: 1 unbalanced stereo/balanced mono, $1Vpp/33k\Omega$ on a 3.5mm mini jack. OUTPUTS: 5 unbalanced stereo/balanced mono, $1Vpp/50\Omega$ on 3.5mm mini jacks.

MAX. OUTPUT: 5Vpp. AUDIO BANDWIDTH (-3DB): 20kHz.

S/N RATIO: 80dB unweighted.

CONTROL: Left and right gain rear trimmers (0 to +3.5dB).

COUPLING: AC.

AUDIO THD + NOISE: 0.03% (2nd harmonic). POWER CONSUMPTION: 12V DC, 100mA.

INCLUDED ACCESSORIES: Power supply, mounting bracket.

OPTIONS: RK-3T 19" rack adapter.

PRODUCT DIMENSIONS: 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

PRODUCT WEIGHT: 0.1kg (0.3lbs) approx.

SHIPPING DIMENSIONS: 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

SHIPPING WEIGHT: 0.5kg (1.1lbs) approx.

