



KRAMER ELECTRONICS, Ltd.
www.kramerelectronics.com

671R

DVI Over Fiber Optic Receiver



The 671T is a high-performance fiber optic transmitter for DVI signals. The unit converts a DVI signal to light pulses that are transmitted over one single fiber optic cable to the **671R** receiver that converts them back to a DVI signal.



671R

FEATURES

- Max. Data Rate - Up to 1.65Gbps.
- HDCP Compliant.
- HDTV Compatible.
- HDMI Support - HDMI (V.1.4 with Deep Color, x.v.Color™, Lip Sync, HDMI Uncompressed Audio Channels, Dolby TrueHD, DTS-HD).
- 3D Pass-Through.
- Output - DVI-D signal (on a DVI-I connector).
- System Range - 1700m (5570ft).
- Cable - Multimode fiber optic OM3 cable with SC connectors.
- Compact DigiTOOLS® - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.

TECHNICAL SPECIFICATIONS

INPUTS:	1 optical connector.
OUTPUTS:	DVI connector.
DATA RATE:	Up to 1.65Gbps.
EXTENSION LIMIT:	2000m (>6560 feet) for UXGA (1600x1200) and 1080p.
FIBER-OPTIC CONNECTION:	SC connectors for multimode (OM3) fiber cable.
INDICATOR LEDs:	Video, source, acceptor fiber and on LEDs.
POWER SOURCE:	5V DC, 400mA.
DIMENSIONS:	12cm x 7.95cm x 2.76cm (4.7" x 3.1" x 1.08") W, D, H.
WEIGHT:	0.3kg (0.67lbs) approx.
ACCESSORIES:	2 power supplies (5V/2A), 2 bracket installation kits.
OPTIONS:	RK-3 19" rack adapter. DVI/DVI male-to-male cable.