



673R/T

4-Channel 3G HD-SDI over Single Fiber Optic Transmitter & Receiver



The 673T and 673R are a high-performance fiber optic transmitter and receiver for signals up to 3G HD-SDI, and Dual-Link HD-SDI signals. The 673T converts up to four channels of SDI signals on BNC connectors to an optical signal that is transmitted over a single fiber optic cable. The 673R converts the optical signal back to SDI signals.



673R/T

FEATURES

- **Max. Data Rate** - Up to 3Gbps for each SDI input.
- **SDI Inputs/Outputs** - 4 channels on BNC connectors.
- **HDTV Compatible.**
- **System Range** - 1000m (more than 3200ft).
- **Cable** - A single multi-mode OM3 fiber optic cable with SC connectors.
- **Multi-Standard Operation** - SDI, HD-SDI, 3G HD-SDI and dual link HD-SDI.
- **Reclocking and Equalization per Channel.**
- **Fiber Optic, Source & Input Indication LEDs.**
- **Compact DigiTOOLS®** - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.

TECHNICAL SPECIFICATIONS

INPUTS:	3G HD-SDI/HD-SDI/Dual-link SDI serial video, 75Ω on BNC connectors (673T); 1 optical connector (673R).
OUTPUTS:	1 optical connector (673T); 3G HD-SDI/HD-SDI/Dual-link SDI serial video, 75Ω on BNC connectors (673R).
BANDWIDTH:	Up to 3Gbps for each SDI input.
FIBER OPTIC EXTENSION:	Up to 1000m (>3200ft) for 3G HD-SDI.
INPUT CABLE EQUALIZATION (673T):	140m for HD-SDI, 120m for 3G HD-SDI.
FIBER-OPTIC CONNECTION:	SC connectors for multimode (OM3) fiber cable.
INDICATOR LEDs:	VIDEO, SOURCE, FIBER and ON LEDs.
POWER SOURCE:	5V DC, 520mA (673T); 5V DC, 780mA (673R).
DIMENSIONS:	12cm x 8.0cm x 2.8cm (4.7" x 3.1" x 1.1") W, D, H.
WEIGHT:	0.3kg (0.7lbs) approx. each.
ACCESSORIES:	Power supply, bracket installation kit.
OPTIONS:	RK-3T 19" rack adapter.