




VS-1616D

2x2 to 16x16 Modular Multi-Format Digital Matrix Switcher



The VS-1616D is a high-performance matrix switcher chassis for DVI & HDMI signals. The unit is modular and populated from 2x2 to 16x16 in increments of two inputs and/or two outputs. The chassis includes a power supply, control module and a test module that can monitor and test any input and output in the matrix.

FEATURES

- **Kramer Core™ - FLEXIBLE INFRASTRUCTURE CONVERSION!** Copper, Fiber or Twisted Pair – all can be used at the same time, according to input/output module selection. The matrix receives digital signals from compatible Kramer transmitters, automatically converts between available infrastructure options and sends the signals to compatible Kramer receivers. Kramer Core™ solution is the ultimate in versatility!
- **Max. Data Rate - 3.2Gbps per graphics channel up to 10.4Gbps total.**
- **HDTV Compatible.**
- **HDCP Compliant - With DVI (HDCP) and HDMI modules.**
- **DGKat™ Signal Integration - Kramer's unique technology for converting TMDS as well as control and communication to signals that run over twisted pair cables. We strongly recommend using Kramer DGKat™ cables designed specifically for optimum performance.**
- **Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances.**
- **Modular & Easily Configurable Platform - Input or output module types can be mixed and added in increments of 2 from 2x2 up to 16x16.**
- **Available Modules - DVI, DVI (HDCP), DVI (Dual Link), HDMI, LC Optical & DGKat Twisted Pair (available 2nd quarter 2012).**
- **I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for DVI and HDMI systems.**
- **Flexible Control Options - Front panel, IR remote, RS-232 (K-Router™ Windows®-based software is included), Ethernet.**
- **Front Panel Lockout.**
- **Take Button - Executes multiple switches all at once.**
- **Memory Locations - Stores multiple switches as presets to be recalled and executed as needed.**

- Test Pattern Module - With 4 output resolutions for troubleshooting video problems.
- Worldwide Power Supply - 100–240V AC.
- Standard 19" Rack Mount Size - 4U. Rack "ears" included.



www.kramerelectronics.com

VS-1616D

TECHNICAL SPECIFICATIONS

MAX. DATA RATE:	Up to 3.2Gbps bandwidth per channel (limited by the card installed).
MAX RESOLUTION:	Up to UXGA; 1080p, 1920x1200.
CONTROLS:	Front panel buttons, infrared remote control transmitter, RS-232, Ethernet.
SWITCHING:	Confirm or At Once for immediate switching.
OPERATING TEMPERATURE:	0° to +55°C (32° to 131°F).
STORAGE TEMPERATURE:	-45° to +72°C (-49° to 162°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
POWER CONSUMPTION:	100–240V AC, 50/60Hz, 135VA.
DIMENSIONS:	19" x 14.2" x 4U (W, D, H) rack-mountable.
WEIGHT:	8.1kg (17.9lbs) approx.
ACCESSORIES:	Power cord, infrared remote control transmitter.

CONFIGURATIONS

Input Modules

DVI-IN2-F16	2-Input DVI Card (F-16)
HDCP-IN2-F16	2-Input DVI (HDCP) Card (F-16)
DL-IN1-F16	1-Input DVI Dual Link Card (F-16)
F610-IN2-F16	2-Input DVI over 4LC Fiber Card (F-16)
H-IN2-F16	2-Input HDMI Card (F-16)
DGKat-IN2-F16	2-Input HDMI & RS-232 over DGKat Card (F-16)
F670-IN2-F16	2-Input HDMI over OM3 Fiber Card (F-16)

Output Modules

DVI-OUT2-F16	2-Output DVI Card (F-16)
HDCP-OUT2-F16	2-Output DVI (HDCP) Card (F-16)
DL-OUT1-F16	1-Output DVI Dual Link Card (F-16)
F610-OUT2-F16	2-Output DVI over 4LC Fiber Card (F-16)
H-OUT2-F16	2-Output HDMI Card (F-16)
DGKat-OUT2-F16	2-Output HDMI & RS-232 Input over DGKat Card (F-16)
F670-OUT2-F16	2-Output HDMI over OM3 Fiber Card (F-16)

Module Plate

BLP-F16	Blank Cover Plate for Empty Module Slots
---------	--