



FC-101Net

2-Channel Dante Decoder & PoE Acceptor



FC-101Net is a compact 2-channel Dante™ decoder with 2 balanced mono audio outputs. It enables connecting non-Dante devices, such as amplifiers and powered speakers, to a Dante network and enables volume control. FC-101Net is powered over Ethernet from any standard PoE providing network switch

FEATURES

Dante Network Interface

PoE Acceptor

Input - 2 Dante channels on an RJ-45 connector

Outputs - 2 balanced mono audio on a 3-pin terminal blocks

Output Volume Control

Versatile Control - Via the Dante IP control matrix and Kramer Protocol 3000 via RS-232 connection

Professional, Studio Grade Signal Conversion Technology - Includes the latest generation 32-bit advanced Digital Analog Converter architecture to achieve excellent dynamic performance and improved tolerance to clock jitter. Maintains the quality of the original audio signal with selectable sampling rates up to 96 kHz



KRAMER

TECHNICAL SPECIFICATIONS

Outputs	1 Balanced Stereo Audio / 2 Mono Audio On 2 3-pin terminal blocks
Ports	1 Dante On an RJ-45 connector
Control	Dante IP control matrix and Kramer Protocol 3000
Power	Source 48V DC (PoE) Consumption 100mA
Enclosure	Size Pico TOOL Type Aluminum Cooling Convection ventilaion
Environmental Conditions	Operating Temperature 0° to +40°C (32° to 104°F) Storage Temperature -40° to +70°C (-40° to 158°F) Humidity 10% to 90%, RHL non-condensing
STANDARDS COMPLIANCE	Safety CE
Environmental	RoHs, WEEE
Accessories	Included Bracket set, double-sided adhesive dual lock tape
PRODUCT DIMENSION:	6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96") W, D, H
PRODUCT WEIGHT:	0.1kg (0.2lbs) approx
SHIPPING DIMENSION:	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H
SHIPPING WEIGHT:	0.2kg (0.5lbs) approx

