



FC-22ETH

2-Port Ethernet Controller



The FC-22ETH is a bidirectional RS-232 or RS-485 to Ethernet control signal converter. It allows two RS-232 (or one RS-485 and one RS-232) controllable devices to be controlled via an Ethernet or LAN connection.

FEATURES

- **Ports** - 1 RS-232 and 1 serial (RS-232 or RS-485 selectable), 1 Ethernet.
- **Simultaneous Communication** - With up to 40 PC clients.
- **USB Port** - For firmware upgrades.
- **Compact Kramer TOOLS™** - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3TR rack adapter.



FC-22ETH

TECHNICAL SPECIFICATIONS

PORTS:	1 RS-232 and 1 serial (RS-232/RS-485 selectable) on 3-pin terminal block connectors, 1 Ethernet on an RJ-45 connector.
CONTROLS:	Serial Select button, RS-485 terminator switch, DHCP and Factory Default buttons.
INDICATORS:	Power, Ethernet, Serial 1, Serial I/O, and DHCP status LEDs.
POWER CONSUMPTION:	5V DC, xxmA.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
DIMENSIONS:	
WEIGHT:	
ACCESSORIES:	
OPTIONS:	

