



FC-46xl

HDMI Audio De-embedder



The FC-46xl is a high-performance HDMI audio de-embedder. The unit can de-embed audio from the HDMI input or from the HDMI output Audio Return channel to S/PDIF, TOSLINK® and analog audio outputs simultaneously.

FEATURES

Max. Data Rate - Up to 2.25Gbps.

HDCP Compliant.

HDTV Compatible.

I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.

HDMI Support - HDMI (V.1.4 with ARC, HDMI Uncompressed Audio Channels, Dolby TrueHD, DTS-HD).

Auto Format Detection - Digital RGB or YPbPr.

Compact Kramer TOOLS™ - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.



FC-46xl

TECHNICAL SPECIFICATIONS

INPUT:	1 HDMI connector.
OUTPUTS:	1 HDMI connector, 1 TOSLINK® optical digital audio connector, 1 S/PDIF digital audio on an RCA connector, 1 unbalanced stereo audio on a 3.5mm mini connector.
OPERATION FREQUENCY:	Supports up to 2.25Gbps (1080p @60Hz) 36-bit Deep Color.
COMPLIANCE WITH STANDARDS:	Supports HDMI, HDCP 1.4.
CONTROLS:	Audio source select button.
INDICATOR LEDS:	ON, IN, OUT.
POWER SOURCE:	5V DC, 600mA.
DIMENSIONS:	12.4cm x 7cm x 2.4cm (4.9" x 2.8" x 0.94") W, D, H.
WEIGHT:	0.4kg (0.88lbs) approx.
ACCESSORIES:	Power supply.
OPTIONS:	VA-100P-5 Kramer 10-port universal 5V power supply, RK-3T 19" rack adapter.

