

KDS-DEC3

H.264 Decoder











Kramer KDS-DEC3 is an H.264 decoder for encoded signals up to 1080p60. It is designed to work with the KDS-EN3 H.264 encoder to provide a high-quality and fully-featured end-to-end video and audio over IP solution.

FEATURES

- AVC Support MPEG-4 using H.264 & AAC codecs.
- Scaling & Cropping Features For flexible display of source content on the decoder output.
- Standard Ethernet Network Operation 10/100/1000Mb.
- Decoder-Integrated Network Switch Allows for KDS-DEC3 daisy chaining and network extension.
- Video Support HDMI.
- Audio Support HDMI or analog.
- Streaming Support Unicast and multicast through RTSP (Real Time Streaming Protocol).
- KDS-EN3 Manager Software Allows remote management of the KDS-EN3 network including auto-detection and discovery of KDS-EN3/KDS-DEC3 units on a subnet.
- Fail-safe Video Playback When a decoder loses its connection to an encoder.
- RS-232 Virtualization From encoder to decoder.

TECHNICAL SPECIFICATIONS

OUTPUTS: 1 HDMI, 1 unbalanced stereo audio on a 3.5mm mini jack.

PORTS: 2 Ethernet on RJ-45 connectors (fully switched), 1 RS-232 on a 9-pin D-sub connector.

VIDEO SINGLE

Up to 1920x1080p60 and 1920x1200(60Hz).

CHANNEL HD:

COMPRESSION H.264/Mpeg4 Part 10 (AVC).

STANDARD:

PROFILES: Baseline, Main, High.

LEVELS: Up to 4.2.

BIT RATES: 100Kbps to 25Mbps.

RATE CONTROL: CBR, VBR, adjustable GOP (Group Of Pictures) size.

AUDIO COMPRESSION

STANDARD:

MPEG4 AAC-LC.

CHANNELS: 2 channel (stereo), HDMI with digital L-PCM audio.

ANALOG SAMPLE

32, 44.1, and 48kHz.

FREQUENCY: BIT RATES:

96, 128, 192, and 256Kbps.

OUTPUT RESOLUTIONS: 1920×1200, 1920×1080, 1680×1050, 1600×1200, 1600×900, 1440×900, 1400×1050,

1360×768, 1280×1024, 1280×960, 1280×720, 1024×768, 800×600, 720×576, 720×480, and

640×480.

POWER CONSUMPTION: 5V DC, 3A max.

OPERATING 0° to $+40^{\circ}$ C (32° to 104° F).

TEMPERATURE

STORAGE -40° to $+70^{\circ}$ C (-40° to 158° F).

TEMPERATURE:

HUMIDITY: 10% to 90%, RHL non-condensing.

DIMENSIONS: $12.8 \text{cm} \times 2.6 \text{cm} \times 10.9 \text{cm} (5.05" \times 1.02" \times 4.29").$

WEIGHT: 0.36kg (0.26kg).

INCLUDED Power supply, power cord, plastic bracket set.

ACCESSORIES:

