

KDS-EN4
HD Video Encoder/Streamer

| HDMI | Ethernet - RJ-45



KDS-EN4 is an H.264 encoder for HDMI signals up to 1920x1080p@60Hz. It provides high-quality and fully-featured end-to-end video and audio over IP. KDS-EN4 includes AVC support for H.264/MPEG-4 and AAC codec, open encoding that enables decoding through VLC® player software and unicast streaming through RTSP

FEATURES

AVC Support - H.264/MPEG-4 & AAC codecs

Supported Resolutions - 720p@30Hz, 720p@60Hz, 1080p@30Hz, 1080p@60Hz

Audio Support - Embedded HDMI, unbalanced stereo line in

Standard Ethernet Network Operation - 100/1000Mb

Streaming - Unicast through RTSP (Real Time Streaming Protocol)

Open Encoding - Enables software decoding through VLC® player software



TECHNICAL SPECIFICATIONS

Inputs 1 HDMI On a female HDMI connector

1 Unbalanced Stereo Audio On a 3.5mm mini jack

Ports 1 Ethernet On an RJ-45 connector

2 USB On female USB type-A connectors

2 RS-232 On a five pin terminal block connector

Video Supported Resolutions: 720p@30Hz, 720p@60Hz, 1080p@30Hz, 1080p@60Hz

Compression Standard H.264/MPEG-4 Part 10 (AVC)

Levels Up to 4.2

Bit Rates 100Kbps to 25Mbps

Rate Control CBR

Audio Compression Standard MPEG-4 AAC-LC

Channels 2 channel (stereo), HDMI with digital L-PCM audio

Sample Frequency 44.1, and 48kHz

Bit Rates 128Kbps

Maximum Unicast Connections

8

Power Source 5V DC

Consumption 800mA

Environmental Conditions

Operating Temperature 0° to +40°C (32° to 104°F)

Storage Temperature -40° to +70°C (-40° to 158°F)

Humidity 10% to 90%, RHL non-condensing

Accessories Included Power supply, bracket set

PRODUCT DIMENSION:

12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

PRODUCT WEIGHT: 0.5kg (1.1lbs) approx

