

PC6A-LS5

CAT6A S/FTP 500MHz 4x2x26AWG Patch Cord Low Smoke & Halogen Free



Kramer's PC6ALS5 CAT6A S/FTP patch cord is a highquality LSHF 4x2x26 cable, designed for LAN applications to ensure optimum performance

FEATURES

Quality Construction - 4 twisted pairs of 26AWG stranded copper, each individually screened and overall braided (S/FTP)

RJ-45 Connector - Slim snagless RJ45 connector, 50u gold plated contacts Varied Selection of Lengths - 0.5m to 30m (1.6 to 98ft)



TECHNICAL SPECIFICATIONS

Conductor Material: Annealed copper

Conductor Diameter: 7x0.16 ±0.01mm

Insulation Material: Skin/foam/skin HDPE

Insulation Diameter: 1.0.2±0.1mm

Color Code: Blue/white blue, brown/white brown, orange/white orange, green/white green

Screening Material: Alu/PET per pair

Screening Coverage: >120%

Overall Braiding

Material:

Tinned copper

Braiding Coverage: 40 ±5%

Sheath Material: **LSHF**

Yellow RAL 1018 Sheath Color:

Sheath Diameter: 6.0±0.20mm

Impedance: 1100MHz 100±15,

100250MHz 100±20, 250500MHz 100±25

Max. Conductor DC

Resistance:

<158.8/km

Propagation Velocity: 76%

Mechanical Characteristics: Bending radius - installed: 40mm, during installation: 50mm

Connector Type: Snagless shielded RJ45 CAT5E

Wiring: EIA/TIA 568B

Contact Plating: Gold 50µm

Overmolding: Black, soft PVC

Compliant Standards EIA/TIA 568B, ISO/IEC 11801

- Electrical:

Flammability: IEC 603321, UL CM

Smoke Density: IEC 61034

IEC 60754 Halogen Free:

Environmental: RoHS (2011/65/EU)



CONFIGURATIONS

PC6A-LS503-0.5M	Slim CAT6A S/FTP patch cord cable-LSHF
PC6A-LS503-1M	Slim CAT6A S/FTP patch cord cable-LSHF
PC6A-LS503-2M	Slim CAT6A S/FTP patch cord cable-LSHF
PC6A-LS503-3M	Slim CAT6A S/FTP patch cord cable-LSHF
PC6A-LS503-5M	Slim CAT6A S/FTP patch cord cable-LSHF
PC6A-LS503-10M	Slim CAT6A S/FTP patch cord cable-LSHF
PC6A-LS503-15M	Slim CAT6A S/FTP patch cord cable-LSHF
PC6A-LS503-20M	Slim CAT6A S/FTP patch cord cable-LSHF
PC6A-LS503-30M	Slim CAT6A S/FTP patch cord cable-LSHF