

## RC-76R

6-Button Room Controller





The RC-76R is a six-button configurable room controller for multimedia rooms. It controls audio components, video components and other room facilities such as lights and screens.

## **FEATURES**

- 6 Configurable Buttons RGB backlit, front panel buttons, configured using the K-Config configuration software.
- 1 GPI/O Port Can be configured by K-Config as a digital input, digital output or analog input for interfacing with a variety of devices such as sensors, switches, LEDs, or relays.
- 2 Bidirectional RS-232 Ports Control AV equipment such as projectors, LCD and PDP displays, power amplifiers, switchers and scalers.
- 2 Relay Contact Closure Ports Control other room items related to the AV system, such as, raising and lowering drapes, a screen or a projector.
- 2 IR Control Ports With an IR learning receiver behind the front plate that learns commands from any IR remote.
- 1 RS-485 Port.
- Kramer Site-CTRL Compatibility For network remote control and management over the Ethernet port.
- K-NET™ Control Channel Connects compatible user interfaces, supply power and control data over a single cable.
- Flexible Control Via Ethernet and K-NET.
- Wall Plate Size 1 gang US, Decora compatible.

## RC-76R

## **TECHNICAL SPECIFICATIONS**

INPUTS: 2 RS-232, 1 RS-485, 1 GPI/O and 1 K-NET on terminal block connectors; 1 Ethernet on an

RJ-45 connector; 1 USB for programming.

OUTPUTS: 2 IR, 2 relays (36V AC or DC, 2A, 60VAC maximum on non-inductive load) and 1 GPI/O on

terminal block connectors.

DEFAULT IP SETTINGS: IP number - 192.168.1.39; Mask - 255.255.0.0; Gateway - 0.0.0.0.

POWER CONSUMPTION: 12V DC, 260mA.

OPERATING  $0^{\circ}$  to +40°C (32° to 104°F).

TEMPERATURE:

STORAGE -40° to +70°C (-40° to 158°F).

TEMPERATURE:

HUMIDITY: 10% to 90%, RHL non-condensing.

DIMENSIONS: 7.9cm x 2.8cm x 12.4cm (3.1" x 1.1" x 4.9") W, D, H (with wall plate).

WEIGHT: 0.6kg (1.4lbs) approx.

ACCESSORIES: Power supply, black and white front plates, black and white Decora frames.

