



# KRAMER

## **TBUS-1-KWC**

TBUS with Wireless Charging Spot

---



Kramer's TBUS1KWC is an enclosure of TBUS1A with an integrated, surface mount, wireless charging spot flushmounted on the TBUS bezel

### **FEATURES**

---

**Integrated Wireless Charging Spot** - For mobile phones integrated in the TBUS

**Flush Surface**

**Power Supply** - Requires a supply voltage of 24V DC at 500mA

**Current Input** - 1A, IEEE 802.15.4 based RF channels

**Power Output** - 6 to 15W

**Regulatory Compliance** - PMA type 3 compliant, FCC Title 47, Part 18

EMC Emission EN5502/CISPR22, FCC part 15B

Safety EN609501, EN609501, UL609501, IEC 609501, RoHS, REACH



# KRAMER

## TECHNICAL SPECIFICATIONS

---

POWER SOURCE:	International power sockets available from 110V to 240V AC
FUSE RATING:	T 6.3A 250V
POWER CONSUMPTION:	Charging spot: 5V DC, 1A
SAFETY REGULATORY COMPLIANCE:	CE, FCC
OPERATING TEMPERATURE RANGE:	0° to +40°C (32° to 104°F)
OPERATING HUMIDITY RANGE:	10 to 90% RHL, noncondensing
STORAGE TEMPERATURE RANGE:	40° to +70°C (40° to 158°F)
STORAGE HUMIDITY RANGE:	5 to 95% RHL, noncondensing
DIMENSIONS:	22.1cm x 18.2cm x 13cm (8.17"x 5.88" x 5.13") W, D, H
WEIGHT:	Gross weight: 2.3kg (5.07lbs) approx. TBUS1KWC with table clamps: 1.75kg (3.6lbs) approx. Metal template: 0.125kg (0.28lbs) approx
ACCESSORIES:	Power cord, six selflocking ties, metal template, 1 KWCMUSB, 1 KWCLTN (see separate specifications), power supply, power supply bracket
OPTIONS:	Inner frames, passive wall plates and interfaces, power socket kits, power supply, bracket for power supply



# KRAMER

## CONFIGURATIONS

---

TBUS-1-KWC(B)	TBUS with Wireless Charging Spot - Black
TBUS-1-KWC(BC)	TBUS with Wireless Charging Spot - Brushed Clear