



TP-581T

HDMI, Bidirectional RS-232, Ethernet & IR over Twisted Pair Transmitter



The TP-581T is a high-quality twisted pair transmitter for HDMI, Ethernet 100BaseT, bidirectional RS-232 and IR signals. The TP-581T takes the HDMI input, and converts it with the Ethernet 100BaseT, RS-232 and IR input signals to a twisted pair signal. The TP-582R converts the twisted pair signal back to Ethernet 100BaseT, RS-232, IR and two HDMI outputs, and de-embeds the audio to S/PDIF and TOSLINK® audio outputs.

FEATURES

Max. Data Rate - 2.25Gbps.

HDBaseT Technology.

HDTV Compatible.

HDCP Compliance.

HDMI Support - HDMI (V.1.4 with Deep Color, x.v.Color™, Lip Sync, HDMI Uncompressed Audio Channels, Dolby TrueHD, DTS-HD, CEC).

3D Pass-Through.

EDID PassThru - Passes EDID/HDCP signals from source to display.

Bidirectional RS-232 Interface - Commands and data can flow in both directions via the RS-232 interface, allowing status requests and control of the destination unit.

Ethernet Interface - Passes 100BaseT.

System Range - Up to 100m (330ft).

Cable - Requires shielded twisted pair (STP) cable. For optimum range and performance use, use Kramer's BC-DGKat524, BC-DGKat623 and BC-DGKat723 cables. Note that the transmission range depends on the signal resolution, graphics card and display used. The distance using non-Kramer CAT 5, CAT 6, and CAT 7 cables may not reach these ranges. Use only shielded cable where both ends of the shield are soldered to ground.

Control - Front panel.

Indicators - Status LEDs for input selection, output, link and power.

Compact MegaTOOLS® - 2 units can be rack mounted side-by-side in a 1U rack space with the optional RK-T2B universal rack adapter.



TP-581T

TECHNICAL SPECIFICATIONS

| | |
|--------------------------------|--|
| INPUTS: | 1 HDMI connector, 1 IR on a 3.5mm mini jack, 1 Ethernet 100BaseT on an RJ-45 connector, 1 RS-232 on a 9-pin D-sub connector. |
| OUTPUTS: | 1 RJ-45 connector. |
| BANDWIDTH: | Supports up to 2.25Gbps bandwidth per graphic channel. |
| COMPLIANCE WITH HDMI STANDARD: | Supports HDMI and HDCP. |
| POWER SOURCE: | 5V DC, 800mA. |
| DIMENSIONS: | 18.8cm x 11.4cm x 2.4cm (7.4" x 4.5" x 1.0") W, D, H. |
| WEIGHT: | 0.6kg (1.4lbs). |
| ACCESSORIES: | Power supply. |
| OPTIONS: | RK-T2B 19" rack mount. |

