



TP-582R

1:2 HDMI Plus Bidirectional RS-232, Ethernet & IR over Twisted Pair Receiver



The TP-582R is a high-quality twisted pair receiver for HDMI, Ethernet 100BaseT, bidirectional RS-232 and IR signals. The TP-582T selects one of two HDMI inputs, and converts it with the Ethernet 100BaseT, RS-232 and IR input signals to a twisted pair signal. The TP-582R converts the twisted pair signal back to Ethernet 100BaseT, RS-232, IR and two HDMI outputs, and de-embeds the audio to S/PDIF and TOSLINK® audio outputs.

FEATURES

Max. Data Rate - 2.25Gbps.

HDBaseT Technology.

HDTV Compatible.

HDCP Compliance.

HDMI Support - HDMI (V.1.4 with Deep Color, x.v.Color™, Lip Sync, HDMI Uncompressed Audio Channels, Dolby TrueHD, DTS-HD, CEC).

3D Pass-Through.

EDID PassThru - Passes EDID/HDCP signals from source to display.

Bidirectional RS-232 Interface - Commands and data can flow in both directions via the RS-232 interface, allowing status requests and control of the destination unit.

Ethernet Interface - Passes 100BaseT.

System Range - Up to 100m (330ft).

Cable - Requires shielded twisted pair (STP) cable. For optimum range and performance use, use Kramer's BC-DGKat524, BC-DGKat623 and BC-DGKat723 cables. Note that the transmission range depends on the signal resolution, graphics card and display used. The distance using non-Kramer CAT 5, CAT 6, and CAT 7 cables may not reach these ranges. Use only shielded cable where both ends of the shield are soldered to ground.

Control - Front panel.

Indicators - Status LEDs for input selection, output, link and power.

Compact MegaTOOLS® - 2 units can be rack mounted side-by-side in a 1U rack space with the optional RK-T2B universal rack adapter.



TP-582R

TECHNICAL SPECIFICATIONS

INPUTS:	1 RJ-45 connector.
OUTPUTS:	2 HDMI connectors, 1 IR on a 3.5mm mini jack, 1 Ethernet 100BaseT on an RJ-45 connector, 1 RS-232 on a 9-pin D-sub connector, 1 TOSLINK® optical audio, 1S/PDIF in an RCA connector.
BANDWIDTH:	Supports up to 2.25Gbps bandwidth per graphic channel.
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP.
POWER SOURCE:	5V DC, 1.55A.
DIMENSIONS:	18.8cm x 11.4cm x 2.4cm (7.4" x 4.5" x 1.0") W, D, H.
WEIGHT:	0.6kg (1.4lbs).
ACCESSORIES:	Power supply.
OPTIONS:	RK-T2B 19" rack mount.

