



## TP-582T

2x1 HDMI Plus Bidirectional RS-232, Ethernet & IR over Twisted Pair Switcher/Transmitter



The TP-582T is a high-quality twisted pair transmitter for HDMI, Ethernet 100BaseT, bidirectional RS-232 and IR signals. The TP-582T selects one of two HDMI inputs, and converts it with the Ethernet 100BaseT, RS-232 and IR input signals to a twisted pair signal. The TP-582R converts the twisted pair signal back to Ethernet 100BaseT, RS-232, IR and two HDMI outputs, and de-embeds the audio to S/PDIF and TOSLINK® audio outputs.

## FEATURES

**Max. Data Rate** - 2.25Gbps.

**HDBaseT Technology.**

**HDTV Compatible.**

**HDCP Compliance.**

**HDMI Support** - HDMI (V.1.4 with Deep Color, x.v.Color™, Lip Sync, HDMI Uncompressed Audio Channels, Dolby TrueHD, DTS-HD, CEC).

**3D Pass-Through.**

**EDID PassThru** - Passes EDID/HDCP signals from source to display.

**Bidirectional RS-232 Interface** - Commands and data can flow in both directions via the RS-232 interface, allowing status requests and control of the destination unit.

**Ethernet Interface** - Passes 100BaseT.

**System Range** - Up to 100m (330ft).

**Cable** - Requires shielded twisted pair (STP) cable. For optimum range and performance use, use Kramer's BC-DGKat524, BC-DGKat623 and BC-DGKat723 cables. Note that the transmission range depends on the signal resolution, graphics card and display used. The distance using non-Kramer CAT 5, CAT 6, and CAT 7 cables may not reach these ranges. Use only shielded cable where both ends of the shield are soldered to ground.

**Control** - Front panel and contact closure switching.

**Indicators** - Status LEDs for input selection, output, link and power.

**Compact MegaTOOLS®** - 2 units can be rack mounted side-by-side in a 1U rack space with the optional RK-T2B universal rack adapter.



## TP-582T

### TECHNICAL SPECIFICATIONS

INPUTS:	2 HDMI connectors, 1 IR on a 3.5mm mini jack, 1 Ethernet 100BaseT on an RJ-45 connector, 1 RS-232 on a 9-pin D-sub connector, 1 remote contact closure on a terminal block connector.
OUTPUT:	1 RJ-45 connector.
BANDWIDTH:	Supports up to 2.25Gbps bandwidth per graphic channel.
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP.
POWER SOURCE:	5V DC, 800mA.
DIMENSIONS:	18.8cm x 11.4cm x 2.4cm (7.4" x 4.5" x 1.0") W, D, H.
WEIGHT:	0.6kg (1.4lbs).
ACCESSORIES:	Power supply.
OPTIONS:	RK-T2B 19" rack mount.

