



KRAMER ELECTRONICS, Ltd.
www.kramerelectronics.com

TP-954

DVI & Audio over Twisted Pair Receiver



The **TP-954** is a receiver for twisted pair signals. The TP-953 converts DVI and unbalanced stereo, S/PDIF, or TOSLINK® audio signals to a twisted pair signal and the TP-953 converts the twisted pair signal back into DVI and unbalanced stereo S/PDIF and TOSLINK® audio simultaneously.



TP-954

FEATURES

- Max. Data Rate - 1.65Gbps.
- Max. Resolution - WUXGA & 1080p.
- HDTV Compatible.
- HDCP Compliant
- Inputs - 2 CAT 5.
- Audio Outputs - Stereo, S/PDIF, TOSLINK®.
- EQ (Gain) - On/off select.
- Video Output - 1 DVI.
- Indicator LEDs - Input & Output.
- System Range - Up to 90m (295ft) at XGA or up to 30m (98ft) at WUXGA on shielded BC-DGKat524 cable.
Up to 60m (197ft) at SXGA on shielded BC-DGKat623 cable.
Up to 60m (197ft) at SXGA on shielded BC-DGKat723 cable.
- Cable - Requires shielded twisted pair (STP) cable. For optimum range and performance use, use Kramer's BC-DGKat524, BC-DGKat623 and BC-DGKat723 cables. Note that the transmission range depends on the signal resolution, graphics card and display used. The distance using non-Kramer CAT 5, CAT 6, and CAT 7 cables may not reach these ranges. Use only shielded cable where both ends of the shield are soldered to ground.
- Compact MultiTOOLS® - 4 units can be rack mounted side-by-side in a 1U rack space with the optional RK-1 universal rack adapter.

TECHNICAL SPECIFICATIONS

INPUTS:	2 CAT 5 IN on RJ-45 connectors.
OUTPUTS:	1 DVI on a 24-pin Molex connector, 1 analog audio on a 3.5mm mini jack, 1 S/PDIF on a RCA connector, 1 optical on a TOSLINK® connector.
MAX. DATA RATE:	Supports up to 1.65Gbps per graphic channel.
CONTROLS:	EQ. select pushbutton.
INDICATORS:	IN, OUT, ON LEDs (green).
POWER SOURCE:	12V DC, 380mA.
DIMENSIONS:	10.7cm x 10.4cm x 4.4cm (4.2" x 4.1" x 1.7") W, D, H.
WEIGHT:	0.33kg (0.73lbs).
ACCESSORIES:	Power supply.
OPTIONS:	19" rack mount adapter.