



## VM-216H (previously VM-216HDMI)

2x1:16 HDMI Distribution Amplifier



The VM-216H is a distribution amplifier for HDMI signals. It reclocks and equalizes one of 2 selectable input signals and distributes it to 8 or 16 identical outputs.

### FEATURES

- Max. Data Rate - 2.25Gbps.
- HDTV Compatible.
- HDCP Compliant.
- HDMI Support - HDMI (V.1.4 with Deep Color, x.v.Color™, Lip Sync, CEC).
- 3D Pass-Through.
- Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.
- Control - RS-232.
- Active Output LED Indicators.
- Worldwide Power Supply - 100-240V AC.
- Standard 19" Rack Mount Size - 1U.



## VM-216H (previously VM-216HDMI)

---

### TECHNICAL SPECIFICATIONS

---

INPUTS:	2 on HDMI connectors.
OUTPUTS:	16 on HDMI connectors.
BANDWIDTH:	Supports up to 2.25Gbps bandwidth per graphic channel.
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP.
CONTROLS:	EDID, IN 1, IN 2, IR remote controller and LOCK buttons.
INDICATOR LEDs:	Output status LEDs.
POWER SOURCE:	100-240V AC, 50/60Hz, 48VA.
DIMENSIONS:	19" x 7" x 1U W, D, H, rack mountable.
WEIGHT:	2.5kg (5.5lbs) approx.
ACCESSORIES:	Power cord, IR remote control transmitter.
OPTIONS:	HDMI/HDMI male-to-male cables, Fiber Optic HDMI Cable (C-FOHM/FOHM).