



VM-22H (previously VM-22HDMI)

2x1:2 HDMI Distribution Amplifier



The VM-22H is a distribution amplifier for HDMI signals. The unit reclocks and equalizes one of 2 selectable input signals and distributes it to 2 identical outputs.



VM-22H (previously VM-22HDMI)

FEATURES

- **Max. Data Rate** - 2.25Gbps.
- **HDCP Compliant.**
- **HDMI Support** - HDMI (V.1.4 with Deep Color, x.v.Color™, Lip Sync, CEC).
- **3D Pass-Through.**
- **I-EDIDPro™ Kramer Intelligent EDID Processing™** - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.
- **Active Output LED Indicators.**
- **Control** - Front panel or IR remote switching.
- **Kramer Equalization & re-Klocking™ Technology** - Rebuilds the digital signal integrity to travel longer distances.
- **Compact DigiTOOLS®** - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.

TECHNICAL SPECIFICATIONS

INPUTS:	2 HDMI connectors.
OUTPUTS:	2 HDMI connectors.
BANDWIDTH:	Supports up to 2.25Gbps bandwidth per graphic channel.
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP.
CONTROLS:	EDID SETUP button, input select button, IR.
INDICATOR LEDs:	IN 1, IN 2, OUT 1, OUT 2, and ON LEDs.
POWER SOURCE:	5V DC, 910mA.
DIMENSIONS:	12cm x 7.15cm x 2.44cm (4.7" x 2.8" 0.96") W, D, H.
WEIGHT:	0.3kg (0.67lbs) approx.
ACCESSORIES:	Power supply, bracket installation kit, IR remote control.
OPTIONS:	HDMI/HDMI male-to-male cables.