



VM-28H (previously VM-28HDMI)

2x1:8 HDMI Distribution Amplifier



The VM-28H is a distribution amplifier for HDMI signals. It reclocks and equalizes one of 2 selectable input signals and distributes it to 8 identical outputs.



VM-28H (previously VM-28HDMI)

FEATURES

- Max. Data Rate - 2.25Gbps.
- HDTV Compatible.
- HDCP Compliant.
- HDMI Support - HDMI (V.1.4 with Deep Color, x.v.Color™, Lip Sync, CEC).
- 3D Pass-Through.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.
- Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances.
- Control - RS-232.
- Active Output LED Indicators.
- Worldwide Power Supply - 100-240V AC.
- Standard 19" Rack Mount Size - 1U. Rack "ears" included.

TECHNICAL SPECIFICATIONS

INPUTS:	2 on HDMI connectors.
OUTPUTS:	8 on HDMI connectors.
BANDWIDTH:	Supports up to 2.25Gbps bandwidth per graphic channel.
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI 1.3a and HDCP.
CONTROLS:	EDID, IN 1, IN 2, IR remote controller and LOCK buttons.
INDICATOR LEDs:	Output status LEDs.
POWER SOURCE:	100-240V AC, 50/60Hz 28VA.
DIMENSIONS:	19" x 7" x 1U W, D, H, rack mountable.
WEIGHT:	2.5kg (5.5lbs) approx.
ACCESSORIES:	Power cord, IR remote control transmitter.
OPTIONS:	HDMI/HDMI male-to-male cables, fiber optic HDMI Cable (C-FOHM/FOHM), external remote IR receiver cable.