



KRAMER

VM-2UHD

1:2 4K60 4:2:0 HDMI DA

| HDMI | 4K/60 UHD (4:2:0)



The VM2UHD is a 1:4 distribution amplifier for 4K@60Hz (4:2:0) HDMI 2.0 signals complying with the HDCP 1.4 content protection standard. The unit takes one HDMI input, equalizes and reclocks the signal and distributes it to two identical outputs

FEATURES

Transmitted Data Bandwidth - 10.2Gbps (3.4Gbps per graphic channel)

Video Resolution - Up to 4K@60Hz (4:2:0)

HDMI Signal Transmission - HDMI 2.0 and HDCP 1.4 compliant signal, supporting deep color, x.v.Color™, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS HD, CEC (OUT 1 only), 2K, 4K, and 3D

Auto Outputs Turnon/off - All outputs are turned on when input signal is detected and are turned off automatically, after userselected delay, when no active input signal is detected

IEDIDPro™ Kramer Intelligent EDID Processing™ - An intelligent EDID selection, handling, locking, processing and passthrough algorithm ensures Plug and Play operation for HDMI source and display systems

Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances

Field Maintenance - MiniUSB connection for simple field firmware upgrade with Kramer KUpload tool, easy EDID handling with Kramer EDIDDesigner tool, status indicators for HDMI input and output connected signals, and power indicator, for ease of maintenance and troubleshooting



KRAMER

TECHNICAL SPECIFICATIONS

INPUT:	1 HDMI connector
OUTPUTS:	2 HDMI connectors
PORT:	1 USB for firmware upgrade
MAX. DATA RATE:	10.2Gbps (3.4Gbps per graphic channel)
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP
CONTROLS:	EDID Setup button
INDICATOR LEDs:	IN, OUT 1 and 2 LEDs
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	40° to +70°C (40° to 158°F)
HUMIDITY:	10% to 90%, RHL noncondensing
PRODUCT DIMENSION:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
PRODUCT WEIGHT:	0.2kg (0.4lbs) approx
SHIPPING DIMENSION:	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H
SHIPPING WEIGHT:	0.8kg (1.8lbs) approx
POWER CONSUMPTION:	5V DC, 800mA
INCLUDED ACCESSORIES:	Power supply

