



VM-4HDCPxI

1:4 DVI Distribution Amplifier



The VM-4HDCPxI is a high-performance distribution amplifier for DVI signals. The unit reclocks and equalizes one input signal and distributes it to four identical outputs.

FEATURES

Max. Data Rate - 2.25Gbps.

Max. Resolution - Up to UXGA & 1080p.

HDTV Compatible.

HDCP Compliant.

I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for DVI systems.

Worldwide Power Supply - 100–240V AC.

Standard 19" Rack Mount Size - 1U. Rack "ears" included.



VM-4HDCCPxI

TECHNICAL SPECIFICATIONS

INPUT: 1 DVI, 1.2Vpp on a DVI Molex 24-pin (F) connector; DDC signal 5Vpp (TTL).

OUTPUTS: 4 DVI, 1.2Vpp on DVI Molex 24-pin (F) connectors; DDC signal 5Vpp (TTL).

BANDWIDTH: Supports up to 2.25Gbps bandwidth per graphic channel.

CONTROLS: EDID SELECT, EDID READ.

INDICATOR LEDs: OUTPUT STATUS LEDs.

POWER SOURCE: 100–240V AC, 50/60Hz 17VA.

DIMENSIONS: 19" x 7" x 1U W, D, H, rack mountable.

WEIGHT: 2.5kg (5.5lbs) approx.

ACCESSORIES: Power cord, rack "ears".

OPTIONS: DVI/DVI male-to-male cables, Fiber Optic DVI Cable (C FODM/FODM).

