



VP-409

Video to Computer Graphics Video ProScale™ Digital Scaler (up to WUXGA)



The VP-409 is a high-quality video scaler for composite and s-Video (Y/C) video signals. The unit scales the video to a selectable computer graphics video output signal on a 15-pin HD connector.

FEATURES

- CV and Y/C Inputs.
- Multi-Standard - PAL (B/D/G/H/I) & NTSC (3.58/4.43).
- Output Resolutions - VGA, SVGA, XGA, 1280x800, 1366x768, WSXGA, SXGA, 1400x1050, 1680x1050, UXGA, 1920x1080, and WUXGA.
- Built-in De-interlacer and Comb Filter.
- Non-Volatile Memory - Retains last settings.
- Controls - Front panel buttons for choosing input signal and output resolution.
- External DC Power Source.
- Compact Kramer TOOLS™ - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.



VP-409

TECHNICAL SPECIFICATIONS

INPUTS:	1 CV 1Vpp/75Ω on an RCA connector; 1 Y/C 1Vpp (Y); 0.3Vpp (C)/75Ω on a 4-pin connector.
OUTPUT:	1 VGA (VGA through WUXGA) on a 15-pin HD computer graphics video connector.
OUTPUT RESOLUTIONS:	VGA, SVGA, XGA, 1280x800, 1366x768, WSXGA, SXGA, 1400x1050, 1680x1050, UXGA, 1920x1080, and WUXGA.
OUTPUT REFRESH RATE:	60Hz.
CONTROLS:	Pushbuttons and LEDs for selection of input source and output resolution.
POWER SOURCE:	5V DC, 450mA.
DIMENSIONS:	12cm x 7.5cm x 2.5cm (4.7" x 2.95" x 0.98") W, D, H.
WEIGHT:	0.3kg (0.67lbs) approx.
ACCESSORIES:	Power supply.
OPTIONS:	RK-3T 19" rack adapter.

