



VP-770

8-Input ProScale™ Presentation Switcher/Scaler



The VP-770 is a high-performance presentation switcher and scaler for composite video, component video, DisplayPort, computer graphics video, and HDMI signals. It scales the video, embeds the audio and outputs the signal to HDMI, computer graphics and DGKat twisted pair, together with digital audio, unbalanced stereo and a 10-watt amplified balanced stereo speaker output.



VP-770

FEATURES

- **K-IIT XL™ Picture-in-Picture Image Insertion Technology** - Ultra-stable picture-in-picture, picture-and-picture, and split screen capability. Any video source can be inserted into or positioned next to a computer graphics video source or vice versa with window positioning and sizing controls.
- **K-Storm™ Scaling Technology** - Kramer's extremely high performance scaling technology for converting the incoming video signal with a minimum of motion artifacts. Up- and down-scaling of computer graphics video signals is possible.
- **Ultra-Fast Fade-Thru-Black (FTB™) Switching** - Video switching transitions are clean and ultra fast. The video fades to black and the new input fades from black for smooth, glitch-free switching. The output signal provides constant sync so the display never glitches.
- **Advanced EDID Management** - For each input and analysis of the EDID of a selectable master connection to one of the outputs.
- **HDTV Compatible.**
- **HDCP Compliant** - The HDCP (High Definition Content Protection) license agreement allows copy-protected data on the HDMI input to pass only to the HDMI output.
- **Video Inputs** - Component (Y, Pb, Pr) video on RCA connectors, DisplayPort (DP), 2 computer graphics on 15-pin HD connectors, 2 composite video on RCA connectors and 2 HDMI.
- **Scaled Outputs** - HDMI, computer graphics on a 15-pin HD connector and DGMat twisted pair on an RJ-45 connector simultaneously.
- **Multiple Output Resolutions** - Up to 2K and 1080p.
- **HDMI Deep Color Support.**
- **Luma Keying** - Via PIP window.
- **Vertical Keystoning.**
- **Built-in ProcAmp** - Color, sharpness, contrast, brightness and gamma are set individually for each input.
- **3D Comb Filtering** - Provides the best quality color separation for composite video inputs.
- **Built-in Time Base Corrector** - Stabilizes unstable video sources.
- **Powerful Noise Reduction Filters** - Temporal, block, mosquito and combing.
- **Picture Zooming** - Up to 1600% both on main and PIP picture.
- **De-interlacing** - 3:2 and 2:2 pull-down; 24sf handling.
- **Multiple Aspect Ratio Selections** - Follow input, follow output, best fit, letterbox and overscan.
- **Dual Window Display** - Preset picture-in-picture, picture-and-picture and split screens, as well as customized window layouts.
- **Audio Inputs** - 2 HDMI, 2 computer graphics and 1 DisplayPort and 1 microphone in on 3.5mm mini jacks; 2 CV and 1 S/PDIF on RCA connectors.
- **Audio Outputs** - 1 S/PDIF on an RCA connector, 1 unbalanced stereo audio on a 3-pin terminal block connector and a 2x10W built-in power amplifier with speaker outputs on terminal block connectors.
- **Input and Output Audio Level Adjustment.**
- **Audio Delay** - For lip-sync correction.
- **Selectable Power Saving Modes** - For efficient energy usage.
- **Microphone Input** - Supports mix and talk-over features, as well as delay to prevent feedback.
- **Non-Volatile Memory** - Saves final settings.
- **Firmware Upgrades** - Via Ethernet and RS-232.
- **Flexible Control Options** - Front panel buttons, contact closure, OSD (on-screen display) via front panel buttons or IR remote (remote control included).
- **Worldwide Power Supply** - 100-240V AC.
- **Standard 19" Rack Mount Size** - 1U. Rack "ears" included.



VP-770

TECHNICAL SPECIFICATIONS

INPUTS:	2 HDMI connectors, 2 VGA on 15-pin HD connectors, 1 component video on 3 RCA connectors, 2 composite video on RCA connectors, 1 DisplayPort connector, 2 HDMI, 2 VGA, 1 DP, 2 CV unbalanced stereo audio on 3.5mm mini jack connectors, 1 S/PDIF (for component video input) digital audio on an RCA connector, 1 mic on a 3.5mm mini jack connector.
OUTPUTS:	1 VGA on a 15-pin HD connector, 1 HDMI connector, 1 DGKat on an RJ-45 connector, 1 S/PDIF digital audio on an RCA connector, 1 unbalanced stereo audio on a 3-pin terminal block connector, 1 10W speaker amplifier balanced stereo audio on terminal block connectors.
COMPLIANCE WITH STANDARDS:	Supports HDMI and HDCP; DisplayPort 1.1a.
OUTPUT RESOLUTIONS:	640x480@60, 640x480@75, 800x600@50, 800x600@60, 800x600@75, 1024x768@50, 1024x768@60, 1024x768@75, 1280x768@50, 1280x768@60, 1280x800@60, 1280x1024@50, 1280x1024@60, 1280x1024@75, 1360x768p60, 1366x768@50, 1366x768@60, 1400x1050@50, 1400x1050@60, 1600x900@60, 1600x1200@50, 1600x1200@60, 1680x1050@60, 1920x1200@60, 480i60, 480p60, 576i50, 576p50, 720p50, 720p59.94, 720p60, 1080p23.976, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60, 2048x1080@60Hz, 2048x1080@50Hz.
CONTROLS:	Front panel buttons, OSD, IR remote control, RS-232 on a 9-pin D-sub connector, Ethernet, contact closure.
POWER CONSUMPTION:	100-240V AC, 56VA max.
DIMENSIONS:	19" x 9.3" x 1U (W, D, H) rack mountable.
WEIGHT:	2.5kg (5.5lbs) approx.
ACCESSORIES:	Power cord, rack "ears", IR remote control, control application program via RS-232 (PC) or the Ethernet.



VP-770

