



## VS-211H

2x1 Automatic HDMI Standby Switcher

---



The **VS-211H** is a high-performance automatic standby switcher for HDMI video signals. The unit automatically switches to the secondary input whenever the primary video signal is interrupted. If the primary signal reappears, the unit automatically switches back to the primary input.

### FEATURES

---

Max. Data Rate - Up to 2.25Gbps.

HDTV Compatible.

HDCP and HDMI Compliant.

Active Switching - Automatically switches to the secondary input when the primary is lost, and back to the primary when it is detected.

Primary Input Selector Switch.

Contact Closure - For remote manual switching override.

Compact DigiTOOLS® - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.



## VS-211H

---

### TECHNICAL SPECIFICATIONS

---

INPUTS:	2 HDMI on HDMI connectors.
OUTPUT:	1 HDMI on an HDMI connector.
DATA RATE:	Supports 2.25Gbps.
STANDARDS COMPLIANCE:	HDCP and HDMI.
CONTROLS:	Contact closure remote control, input default selection switch.
POWER SOURCE:	5V DC, 510mA.
DIMENSIONS:	12cm x 7.2cm x 2.4cm (4.7" x 2.8" x 1.0") W, D, H.
WEIGHT:	0.3kg (0.66lbs).
ACCESSORIES:	Power supply, mounting bracket.
OPTIONS:	RK-3T 19" rack adapter.

