



VS-311H (previously VS-311HDMI)

3x1 HDMI, Stereo & S/PDIF Audio Standby Switcher



The VS-311H is a high-performance switcher for HDMI video and balanced, unbalanced and S/PDIF audio signals. When configured as a standby switcher, it switches to a selectable secondary input upon loss of the primary input.



VS-311H (previously VS-311HDMI)

FEATURES

- Max. Data Rate - Up to 2.25Gbps.
- HDTV Compatible.
- HDCP & HDMI Compliant.
- Flexible Control Options - Automatic (standby), RS-232, Ethernet, contact closure & IR (included).
- Input Priority - Selectable via DIP-switches.
- Desktop Size - Compact size. 2 units can be rack mounted side-by-side in a 1U rack space with the optional RK-1 adapter.

TECHNICAL SPECIFICATIONS

INPUTS: 3 HDMI connectors; 3 S/PDIF digital audio on RCA connectors; 3 unbalanced stereo audio +4dBu on 3.5mm mini jacks.

OUTPUTS: 1 HDMI connector; 1 S/PDIF digital audio on an RCA connector; 1 unbalanced stereo audio +4dBu on a 3.5mm mini jack; 1 balanced stereo audio on a 5-pin detachable terminal block.

DATA RATE: Up to 2.25Gbps.

POWER SOURCE: 12V DC, 270mA.

CONTROLS: Front panel buttons, infrared remote control transmitter, RS-232, Ethernet.

DIMENSIONS: 21.6cm x 16.1cm x 4.4cm (8.5" x 6.3" x 1.7") W, D, H.

WEIGHT: 1.2kg (2.6lbs) approx.

ACCESSORIES: Power supply.

OPTIONS: RK-1 19" rack adapter.