

VS-801USB

8x1 USB2.0 Switcher





The VS-801USB is a high-quality 8x1 USB switcher. It accepts up to eight USB devices and switches the selected device to the host.

FEATURES

- High-Speed USB Ver 2.0.
- Controls 8 device select buttons.
- Flexible Control Options Front panel buttons, RS-232 and Ethernet via K-SINGLE control application software, remote contact closure, IR remote (included).
- Firmware Upgrade Via RS-232 using K-UPLOAD application software.
- Compact MegaTOOLS[™] 2 units can be rack mounted side-by-side in a 1U rack space with the optional RK-T2B universal rack adapter.



VS-801USB

TECHNICAL SPECIFICATIONS

DEVICE PORTS:	8 USB (type A) ports.
HOST PORT:	1 USB (type B) port.
CONTROL:	Front panel buttons, IR remote control, RS-232, Ethernet, remote contact closure terminal block.
POWER	5V DC, 150mA.
CONSUMPTION:	
OPERATING TEMPERATURE:	0° to +55°C (32° to 131°F).
STORAGE TEMPERATURE:	−45° to +72°C (−49° to 162°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
DIMENSIONS:	18.8cm x 11.4cm x 2.4cm (7.4" x 4.5" x 0.9") W, D, H.
WEIGHT:	0.75kg (1.7lbs) approx.
ACCESSORIES:	Power supply, bracket installation kit 1m USB 2.0 A MALE/B MALE (Hi-speed USB cable, Rev 2 shielded 28AWG/1P + 24AWG/2C), P/N 2505-000005.
OPTIONS:	RK-T2B 19" rack adapter.

2

