



WP-110

Active Wall Plate - Computer Graphics Video Transmitter



The **WP-110** is a wall plate twisted pair transmitter for computer graphics video signals with resolutions up to and exceeding UXGA. It converts a computer graphics video signal into a twisted pair signal that the TP-120 twisted pair receiver (or other compatible Kramer receiver) converts back into a computer graphic signal.

Available in Gray, White & Off-White



WP-110

FEATURES

- HDTV Compatible.
- Max. Resolution - WUXGA & 1080p.
- Power Connect™ System - A single connection to the transmitter or the receiver powers both units when the devices are within 50m (150ft) of each other. All the system units must have the Power Connect system to use this feature.
- Advanced Sync Processing - Ensures compatibility with a wide range of computers.
- Front Panel Connection - 15-pin HD (F) input.
- Rear Panel Connection - RJ-45 output.
- Sync Polarity Settings - H & V switches for improved display compatibility with the CAT 5 outputs.
- System Range - Up to 100m (320ft).
- Cable - UTP (unshielded twisted pair) or STP (shielded twisted pair) such as CAT 5.
- Dimensions - 6.9cm x 4.1cm x 11.4cm (2.71" x 1.63" x 4.49") US; 8.6cm x 4.1cm x 8.6cm (3.39" x 1.63" x 3.39") and 8cm x 4.1cm x 8cm (3.15" x 1.63" x 3.15") EU W, D, H.
- Wall Plate Size - 1 gang EU/US.

TECHNICAL SPECIFICATIONS

INPUT:	1 VGA/UXGA on a 15-pin HD connector.
OUTPUTS:	1 RJ-45 LINE OUT connector.
MAX. RESOLUTION:	WUXGA & 1080p.
DIFF. GAIN:	2.9% (worst case).
DIFF. PHASE:	0.3Deg (worst case).
K-FACTOR:	<0.05%.
S/N RATIO:	69dB (worst case).
COUPLING:	AC.
POWER SOURCE:	12V DC, 60mA.
DIMENSIONS:	6.9cm x 4.1cm x 11.4cm (2.71" x 1.63" x 4.49") US; 8.6cm x 4.1cm x 8.6cm (3.39" x 1.63" x 3.39") and 8cm x 4.1cm x 8cm (3.15" x 1.63" x 3.15") EU W, D, H.
WEIGHT:	0.14kg (0.31lbs) approx.
ACCESSORIES:	Power supply.