

## WP-580RXR

Active Wall Plate - HDMI over Extended Range HDBaseT Twisted Pair Receiver











The WP-580RXR is an extended range, HDBaseT twisted pair wall plate receiver for HDMI signals. The WP-580RXR receives an HDBaseT twisted pair signal from the WP-580TXR and converts it back into HDMI signals.

## **FEATURES**

- Max. Data Rate 10.2Gbps (3.4Gbps per graphic channel).
- HDTV Compatible.
- HDCP Compliance.
- HDBaseT™ Technology.
- HDMI Support Deep Color, x.v.Color™, Lip Sync, HDMI Uncompressed Audio Channels, Dolby TrueHD, DTS-HD, CEC.
- 3D Pass-Through.
- EDID PassThru Passes EDID signals between the source and display.
- 2K & 4K Support.
- System Range Up to 130m (430ft) normal mode; up to 180m (590ft) Ultra mode (1080p @60Hz @24bpp) when using BC-DGKat623 cables.
- Ultra Range Up to 180m (590ft) with a resolution of up to 1080p @60Hz at 24 bits per pixel.
- Cable Requires shielded twisted pair (STP) cable. For optimum range and performance use, use Kramer's BC-DGKat524, BC-DGKat623 and BC-DGKat7a23 cables. Note that the transmission range depends on the signal resolution, graphics card and display used. The distance using non-Kramer CAT 5, CAT 6, and CAT 7 cables may not reach these ranges. Use only shielded cable where both ends of the shield are soldered to ground.
- Indicators Status LEDs for input, output, link and power.
- Dimensions 12.4cm x 3.12cm x 7.9cm (4.88" x 1.29" x 3.12") US; 15.1cm x 2.96cm x 8.6cm (5.95" x 1.17" x 3.39"), 15.1cm x 2.96cm x 8.0cm (5.95" x 1.17" x 3.15") EU (W, D, H).
- Wall Plate Size 2 gang EU/US.

## WP-580RXR

## **TECHNICAL SPECIFICATIONS**

INPUTS: 1 HDBaseT twisted pair RJ-45 connector.

OUTPUTS: 1 HDMI connector.

BANDWIDTH: 10.2Gbps (3.4Gbps per graphic channel).

COMPLIANCE WITH HDMI

Supports HDMI and HDCP.

POWER CONSUMPTION: 5V DC, 1.03A.

0° to 40°C (32° to 104°F). **OPERATING** 

TEMPERATURE:

STANDARD:

STORAGE TEMPERATURE: -40° to +70°C (-40° to 158°F).

HUMIDITY: 10% to 90%, RHL non-condensing.

**DIMENSIONS:** 12.4cm x 3.12cm x 7.9cm (4.88" x 1.29" x 3.12") US; 15.1cm x 2.96cm x 8.6cm (5.95" x 1.17"

x 3.39"), 15.1cm x 2.96cm x 8.0cm (5.95" x 1.17" x 3.15") EU (W, D, H).

WEIGHT: 0.6kg (1.4lbs). Power supply. ACCESSORIES:

